



Regular

Dry Chemical

**Manufactured and Tested to
ANSI/UL Standards**

**Amerex is an ISO-9001:2000
Registered Firm**

- ★ Dependable Steel Cylinders
- ★ All Metal Valve Construction
- ★ Easy and less costly to maintain and service
- ★ U/L & U.S. Coast Guard Listed
- ★ Bar Coded Labels

(Temperature Range -65°F to 120°F)

Note: All extinguishers (except Model A620T) are U.S. Coast Guard approved with bracket listed on U.L. label.

Stored Pressure



REGULAR extinguishers contain a siliconized sodium bicarbonate based dry chemical with free flowing and non-caking additives. Economical Class B & C protection with lower initial cost and recharging. This chemical smothers fires in flammable liquids and pressurized gases and will not conduct electricity back to the operator.

Available in Wheeled and Stationary extinguishers.

6 YEAR WARRANTY

SPECIFICATIONS		REGULAR Dry Chemical								
VALVES		ALUMINUM						BRASS, CHROME PLATED		
Size & Capacity (lbs.)	1	2½	5	5½	10 Tall	20	6	10 Tall	20	
Application	Nozzle						Hose and Nozzle			
Model Number	A620T	B403T	B409T	B453	B457	A412	B462	B447	408	
U/L Rating	2B:C	10B:C	10B:C	40B:C	60B:C	120B:C	40B:C	60B:C	120B:C	
Shipping Wt. (lbs.)	2½	5½	9¼	9½	18	38	13¾	19	39	
Height (in.)	10	15½	15¼	15¼	20	23¼	16¼	20½	24	
Width (in.)	3½	5¾	5½	7¼	7¾	10¼	8½	8¾	10¼	
Depth (Diam. - in.)	2¾	3	4¼	4¼	5	7	5	5	7	
Range (ft.)	5 - 8	9 - 15	12 - 18	12 - 18	15 - 21	15 - 21	15 - 21	15 - 21	15 - 21	
Discharge Time (Sec.)	10	10	10	14	18	28	14	18	28	
Available with Chrome Plated Cylinder	Yes	Yes	Yes	Yes						
F. M. Approved		Yes	Yes		Yes	Yes	Yes	Yes	Yes	
Standard Bracket	Vehicle	Vehicle - Marine			Wall					