

Arm-A-Dor® Series

Features

- Deadbolt locking bar members extend 1 1/2" over frame on each side
- Automatic or manual relocking models
- Alarm operated with a variety of standard or interchangeable core mortise cylinders
- Compatible with existing BEST key systems
- Optional remote switch operates timed delay egress systems with cameras or other alarms
- Compatible with time delay access products

Code Conformance

- UL LISTED – Panic and Fire Exit Hardware. UL10C, UBC 7-2, and UL305
- Hurricane Devices – Miami-Dade County Product Control Division has approved Arm-A-Dor® Series A100-INS
- Conforms to NFPA 101, ICC A117.1 section 404.2.6

Alarmed Models

- Battery operated - approx. 1 yr. life; two 9V batteries included
- Low battery audible warning signal
- Loud alarm, 1 piezo horns; 95 db @ 10ft.
- Tamper Alarm
- Nuisance Alarm
- Optional AC adapter with battery back-up
- Re-arm reminder feature



Installation

- Retrofit or new construction work
- One size fits doors 36" to 48" wide
- No special door preparation
- Works on any door and frame
- Non-handed
- Shipped with all required hardware for standard single door applications
- Double-door applications work on fixed or removable center mullions, or without mullions

Mechanical Efficiency and Durability

- Roller design deadbolt means reduced friction and wear
- Touch-bar operates with straight push-through motion
- Weather and water resistant