

Grab Bars



CONFIGURATIONS, DIMENSIONS, FINISHES:

**1 1/2" (38MM) DIA.
STRAIGHT/SATIN**

- ⚡**B-6806x12"** (305mm)
- ⚡**B-6806x18"** (455mm)
- ⚡**B-6806x24"** (610mm)
- ⚡**B-6806x30"** (760mm)
- ⚡**B-6806x36"** (915mm)
- ⚡**B-6806x42"** (1065mm)
- ⚡**B-6806x48"** (1220mm)

**1 1/4" (32MM) DIA.
STRAIGHT/SATIN**

- ⚡**B-5806x18"** (455mm)
- ⚡**B-5806x24"** (610mm)
- ⚡**B-5806x30"** (760mm)
- ⚡**B-5806x36"** (915mm)
- ⚡**B-5806x42"** (1065mm)
- ⚡**B-5806x48"** (1220mm)

**1 1/2" (38MM) DIA.
STRAIGHT/PEENED**

- ⚡**B-6806.99x18"** (455mm)
- ⚡**B-6806.99x24"** (610mm)
- ⚡**B-6806.99x30"** (760mm)
- ⚡**B-6806.99x36"** (915mm)
- ⚡**B-6806.99x42"** (1065mm)

**1 1/4" (32MM) DIA.
STRAIGHT/PEENED**

- ⚡**B-5806.99x18"** (455mm)
- ⚡**B-5806.99x24"** (610mm)
- ⚡**B-5806.99x30"** (760mm)
- ⚡**B-5806.99x36"** (915mm)
- ⚡**B-5806.99x42"** (1065mm)

CONCEALED MOUNTING WITH SNAP FLANGE

- Constructed of 18-gauge (1.2mm), type 304 satin-finish stainless steel tubing in 1 1/4" and 1 1/2" (32 and 38mm) diameters.
- Concealed mounting flange 1/8" (3mm) thick, type 304 stainless steel plate, 2" W x 3 1/8" H (50 x 80mm), with screw holes for concealed anchors.
- Cover is 22-gauge (0.8mm), type 304 stainless steel with satin finish, 3 1/4" (85mm) diameter.
- Cover snaps over mounting flange to conceal screws.
- Peened nonslip gripping surface available.



SERIES	DIAMETER	FINISH*
B-6806*	1 1/2" (38mm)	Satin Finish
B-5806*	1 1/4" (32mm)	Satin Finish

*Peened nonslip gripping surface available. Add suffix .99 to model number.

OPTIONAL MOUNTING KITS

Order one per flange. Part No. ⚡**252-30** (3) sheet-metal screws; **2521-30** (3) machine screws with toggle nuts; **2522-30** (3) machine screws with expansion shields.

OPTIONAL ANCHOR DEVICES

Order one per flange. Part No. **2583** anchors for 3/4" to 1" (19–25mm) panels; **2586** anchors for 1/2" (13mm) panels.



⚡**251-4 WingIt™ GRAB BAR FASTENER**

For 2 1/2" and 3 1/2" (65 and 90mm) or deeper hollow walls with finished wall surfaces 1/4" to 1 1/2" (6 to 38mm) thick. One fastener required for each flange. Corrosion-resistant stainless steel. Install grab bars without backing. The fastener will support 300 lbs (136 kg) load. Patented.

WingIt™ is a trademark of WingIt Innovations, LLC.

**TWO-WALL TUB/
SHOWER TOILET
COMPT.**
24" W x 36" D (61 x 91cm)

- 1 1/2" (38mm) Dia.
- B-68616** Satin
- B-68616.99** Peened
- 1 1/4" (32mm) Dia.
- B-58616** Satin
- B-58616.99** Peened

**TWO-WALL TUB/
SHOWER TOILET
COMPT.**
36" W x 54" D (91 x 137cm)

- 1 1/2" (38mm) Dia.
- ⚡**B-68137** Satin
- B-68137.99** Peened
- 1 1/4" (32mm) Dia.
- B-5837** Satin
- B-5837.99** Peened

TWO-WALL SHOWER
15 7/8" W x 30 7/8" D
(40 x 78cm)

- 1 1/2" (38mm) Dia.
- ⚡**B-6861** Satin
- B-6861.99** Peened

**TWO-WALL
TOILET COMPT.**
42" W x 54" D
(107 x 137 cm)

- 1 1/2" (38mm) Dia.
- ⚡**B-6897** Satin
- B-6897.99** Peened
- 1 1/4" (32mm) Dia.
- B-5897** Satin
- B-5897.99** Peened

SWING UP
29" (74cm) Patented

- 1 1/4" (32mm) Dia.
- B-4998** Satin
- B-4998.99** Peened



GAMCO

SPECIAL GAMCO GRAB BARS WITHOUT THE SPECIAL ORDER

- Customized configurations and dimensions.
- Runs of one to thousands.
- Brass and bronze metallic finishes.
- Electrostatic precise color matching.