

CRL Jackson® 20 Series Rim Panic Exit Devices

- Designed for Use With 1-3/4" (44 mm) Narrow, Medium, and Wide Stile Aluminum, Wood, or Hollow Metal Doors
- Complies with ANSI 156.3, Grade 1 Specifications
- Concealed Fastening for Added Security
- Can Be Cut to Size

For additional product information, visit our web site at crlaurence.com/panic-devices.

SPECIFICATIONS:

2095 Rim Device

- | | |
|---|---|
| <ul style="list-style-type: none"> • Requires Rim Cylinder for Keyed Entry; See Page CH206 for Cylinders • Cylinder Mounting Pad Not Required • 3/4" (19 mm) Throw Deadlocking Latch | MATERIALS: <ul style="list-style-type: none"> • Body and Push Pad: Extruded Aluminum • Mechanical Components: Stainless and Hardened Plated Steel • Latch and Strikes: Sintered Steel |
|---|---|



Model 2095

MORE CHOICES
crlaurence.com

'C' STRIKE

36" (914 MM) DOOR CAT. NO.	48" (1219 MM) DOOR CAT. NO.	HANDING	FINISH
312095LC3628	312095LC4628	Left Hand-Reverse Bevel	Satin Aluminum
312095RC3628	312095RC4628	Right Hand-Reverse Bevel	Satin Aluminum
312095LC3313	312095LC4313	Left Hand-Reverse Bevel	Dark Bronze
312095RC3313	312095RC4313	Right Hand-Reverse Bevel	Dark Bronze

Minimum order: 1 each. All Panic Exit Devices can be combined for quantity pricing.




'C' Strike

'S' STRIKE

36" (914 MM) DOOR CAT. NO.	48" (1219 MM) DOOR CAT. NO.	HANDING	FINISH
312095LS3628	312095LS4628	Left Hand-Reverse Bevel	Satin Aluminum
312095RS3628	312095RS4628	Right Hand-Reverse Bevel	Satin Aluminum
312095LS3313	312095LS4313	Left Hand-Reverse Bevel	Dark Bronze
312095RS3313	312095RS4313	Right Hand-Reverse Bevel	Dark Bronze

Minimum order: 1 each. All Panic Exit Devices can be combined for quantity pricing.



'S' Strike



Cylinder Dogging

Cylinder dogging is available when specified by adding "C" behind the model series number. The Exit Device is supplied with the required prep and special cam only that is required to be used with a 1-1/8" (29 mm) Mortise Cylinder that is not supplied with the device and must be purchased separately. See DC7185SC Series on page CH206. **Example:** 312095'C'LC3628

CRL Jackson® Panic Accessories



MORE INFORMATION
crlaurence.com

For Active Outside Trim and Other CRL Jackson® Panic Accessories, see pages CH081-CH082, and CH206.

UL is a registered trademark of UL LLC.

go to crlaurence.com to search for

panic-devices

Search

or enter the Catalog Number for complete product information

CH078

TOLL Phone: (800) 421-6144
FREE Fax: (800) 262-3299
 From Anywhere in the U.S. or Canada



CRL Jackson® 20 Series Electrified Exit Devices and Accessories

- Remote Locking and Unlocking Capability
- Solenoid Operated Latch Retraction
- Fit Door Stiles as Narrow as 1-3/4" (44 mm)
- For Aluminum or Hollow Metal Doors
- Ideal for Use With Card Access
- Fail-Secure Operation
- Can Be Cut to Size



MORE INFORMATION
crlaurence.com

SPECIFICATIONS:

- Ships Standard for 48" (1219 mm) Wide Door – Field Sizeable
- For Use Down to 36" (914 mm) Wide Doors
- Wear Points Insulated by Nylon Sleeves and Rollers
- Adjusts for Brief or Extended Unlock Mode
- 24V DC Input
- Requires 10 Amp Inrush Power Supply; Jackson® 302616 Power Supply Recommended

2085E, 2086E, and 20861E Concealed Vertical Rod Devices

- Positive Locking, Spring Loaded Top Latch
- Top and Bottom Bolt Action – 1/2" (13 mm) Throw
- Standard Height 84" (2134 mm); See Page CH082 for Extensions
- Requires Mortise Cylinder and No. 30821J Mounting Pad for Keyed Entry; See Pages CH082 and CH206 for Cylinders and Pads
- Impact-Top Bolt Series Includes Aluminum Bolts and Guides

2095E Rim Device

- Requires Rim Cylinder for Keyed Entry; See Page CH206 for Cylinders
- Cylinder Mounting Pad Not Required
- 3/4" (19 mm) Throw Deadlocking Latch

MATERIALS:

- Body and Push Pad: Extruded Aluminum
- Mechanical Components: Stainless and Hardened Plated Steel
- Latch and Strikes: Sintered Steel

ELECTRIFIED CONCEALED VERTICAL ROD DEVICES

TOP LATCH CAT. NO.	TOP BOLT CAT. NO.	IMPACT-TOP BOLT CAT. NO.	HANDING	FINISH
312085ELG628	312086ELG628	3120861EL4628	Left Hand-Reverse Bevel	Satin Aluminum
312085ERG628	312086ERG628	3120861ER4628	Right Hand-Reverse Bevel	Satin Aluminum
312085ELG313	312086ELG313	3120861EL4313	Left Hand-Reverse Bevel	Dark Bronze
312085ERG313	312086ERG313	3120861ER4313	Right Hand-Reverse Bevel	Dark Bronze

Minimum order: 1 each. All Panic Devices can be combined for quantity pricing.

ELECTRIFIED RIM EXIT DEVICE

CAT. NO.	HANDING	FINISH
312095EC4628	Non-Handed	Satin Aluminum
312095EC4313	Non-Handed	Dark Bronze

Minimum order: 1 each. All Panic Devices can be combined for quantity pricing.

CRL Jackson® Electrified Outside Trim

- Designed for Use With Jackson® Exit Devices
- Non-Handed – Field Reversible
- Fail-Secure Operation

FLAT LEVER CAT. NO.	ROUND LEVER CAT. NO.	FOR USE WITH MODEL	FINISH
8500EL02628	8500EL01628	1285 and 2085 CVR	Satin Aluminum
8500EL02313	8500EL01313	1285 and 2085 CVR	Dark Bronze
9500EL02628	9500EL01628	1295 and 2095 RIM	Satin Aluminum
9500EL02313	9500EL01313	1295 and 2095 RIM	Dark Bronze

Minimum order: 1 each. Finishes and styles can be combined for quantity pricing.

SPECIFICATIONS:

- Keyed Entry Requires use of CRL No. DRA10 Mortise Cylinder; (Sold Separately See Page CH026)
- ANSI Function 08 – Key Locks or Unlocks Lever

SOLENOID:

- Input: 24V DC
- Current Inrush Required: 0.25 Amps
- Continuous Holding: 0.30 Amps

MATERIALS:

- Escutcheon: Extruded Aluminum
- Lever: High Tensile Strength Aluminum
- Mechanical Components: Hardened, Plated Steel



CRL Jackson® Power Supply

- Designed for Use With Jackson® Electrified Exit Devices
- 24V DC Output Powers Up to Two Devices
- Provides 10 Amp Inrush and 5 Amp Hold



NOTE: Not for Outdoor Use

CAT. NO. 302616
Minimum order: 1 each.



MAXIMUM WIRE LENGTH PER GAUGE CHART

WIRE GAUGE	MAX. LENGTH
16 AWG	40 ft. (12 m)
14 AWG	60 ft. (18 m)
12 AWG	100 ft. (31 m)

Do Not Exceed Maximum Length.

UL is a registered trademark of UL LLC.

go to crlaurence.com to search for

panic-devices

Search

or enter the Catalog Number for complete product information

CH079

TOLL Phone: (800) 421-6144
FREE Fax: (800) 262-3299
From Anywhere in the U.S. or Canada

