

## CL3700 Series

Light/Medium-Duty Lever Locksets



ASSA ABLOY, the global leader  
in door opening solutions

# Applications/Finishes

## CL3700

### Index

Applications.....	2
Finishes.....	2
Features.....	3
Trim Designs.....	3
Functions.....	4
Options and Accessories .....	5
How to Order/ .....	6-7
Quick Codes	
Specifications.....	7

### Quality

The CL3700 series is a Grade 2 light/medium-duty cylindrical lockset which provides an outstanding combination of value and performance. It is the ideal lever lockset for light commercial and heavy-duty residential applications such as interior offices, closets, multifamily housing, restaurants and retail complexes. Available in six architectural finishes and three lever designs, the CL3700 series provides quality materials and performance.

### Aesthetics

Three lever designs offer variety when deciding on visual appeal, functionality and application. The Newport and Princeton lever designs easily fit into most commercial applications, while the Frascati lever brings a touch of Italy to residential and more sophisticated applications.

### Finishes

Description	
BHMA 605	Bright Brass
BHMA 606	Satin Brass
BHMA 613	Dark Oxidized Satin Bronze, oil rubbed
BHMA 625	Bright Chromium Plated
BHMA 626	Satin Chromium Plated
Zinc levers are plated to match BHMA finish.	

\*Simulated painted finish meeting ANSI standards for wear and durability.

### Vandal Resistance

CL3700 series locksets are available with Corbin Russwin's Pyramid patented security cylinder, the most secure locking system available. Pyramid is especially recommended for installations that require superior protection against picking and drilling. See the Key Systems catalog for additional information.

### Key Advantages

- ANSI Grade 2 certification
- UL 1-1/2 hour fire rating
- Pyramid cylinders for increased security
- Interlocking tubular chassis and latchbolt
- ISO 9001 designed and manufactured in a certified 9001 facility

# Features/Trim Designs

## CL3700

### Features

#### Handing

Field reversible.  
Right or left hand must be specified for Frascati CL3755, 3759, 3780 and 3750.

#### Door Thickness

1-3/8" (35mm) to 1-3/4" (44mm).

#### Lock Chassis

Die-cast zinc for corrosion resistance.

#### Backset

2-3/4" (70mm) standard.  
Optional: 2-3/8" (60mm).

#### Latches

1/2" (13mm) bolt projection.

#### Auxiliary Latchbolt

Deadlocking latchbolt prevents manipulation when door is closed.

#### Strike

"T" Strike standard. Optional strikes, lip lengths and ANSI wrought strike box available; see How to Order, page 6.

#### Cylinder

Brass, 6-pin, L4 keyway, "0" bitted standard.

#### Split Finishes

BHMA 605x625, 605x626, 606x625, and 606x626 are available in CL3720 privacy function only. Outside finish specified first. Front and strike finished to match inside trim unless otherwise specified.

#### Keying Features Available

Master keying  
Construction master keying  
Visual key control  
Concealed key control  
Pyramid

#### Keys

Two nickel silver standard.

#### Warranty

One-year limited.

### Certification/Compliance

#### ANSI

Meets A156.2 Series 4000, Grade 2.  
Meets A117.1 Accessibility Code.

#### California State Reference Code

(Formerly Title 19, California State Fire Marshal Standard)

All levers with returns comply; levers return to within 1/2" of door face.

#### C-UL US

All locks listed for B Label Single doors.  
UL symbol on latch front indicates listing.

Any retrofit or other field modification to a fire rated opening can potentially impact the fire rating of the opening, and Corbin Russwin, Inc. makes no representations or warranties concerning what such impact may be in any specific situation. When retrofitting any portion of an existing fire-rated opening, or specifying and installing a new fire-rated opening, please consult with a code specialist or local code official (Authority Having Jurisdiction) to ensure compliance with all applicable codes and ratings.

## Trim Designs


### Newport NZD



Lever: Die-cast zinc  
Lever length: 5-7/32" (133mm)  
Rose: Brass  
Rose diameter: 2-9/16" (65mm)



Complies with codes requiring lever to return to within 1/2" (13mm) of door face.




### Frascati FZD



Lever: Die-cast zinc  
Lever length: 4-3/4" (121mm)  
Rose: Brass  
Rose diameter: 2-9/16" (65mm)



Complies with codes requiring lever to return to within 1/2" of door face.




### Princeton PZD



Lever: Die-cast zinc  
Lever length: 5-3/16" (132mm)  
Rose: Brass  
Rose diameter: 2-9/16" (65mm)










Complies with codes requiring lever to return to within 1/2" of door face.



# Functions


## CL3700

Outside	Inside	Series/ Function	Type	ANSI No. Series 4000	Function Description
		CL3710	Passage or Closet	F75	<ul style="list-style-type: none"> <li>• Deadlocking latchbolt by lever either side.</li> <li>• Both levers always free.</li> </ul>
		CL3720	Privacy Bedroom or Bathroom	F76	<ul style="list-style-type: none"> <li>• Deadlocking latchbolt by lever either side.</li> <li>• Outside lever locked by button.</li> <li>• Outside lever unlocked by rotating inside lever.</li> <li>• Emergency release in outside lever.</li> <li>• Inside lever always free.</li> </ul>
		CL3751	Entrance or Office	F81/82	<ul style="list-style-type: none"> <li>• Deadlocking latchbolt by lever either side, except when turn button locks outside lever.</li> <li>• Rotating turn button locks outside lever, requiring key to unlock.</li> <li>• Rotating button the other way unlocks outside lever.</li> <li>• Inside lever always free.</li> </ul>
		CL3755	Classroom	F84	<ul style="list-style-type: none"> <li>• Deadlocking latchbolt by lever either side, except when key outside locks outside lever.</li> <li>• Outside lever unlocked by key outside.</li> <li>• Inside lever always free.</li> </ul>
		CL3759	Storeroom or Public Restroom	—	<ul style="list-style-type: none"> <li>• Deadlocking latchbolt by lever inside.</li> <li>• Key outside unlocks outside lever to retract latchbolt.</li> <li>• Lever retracts latchbolt.</li> <li>• Key is retained in the unlocked mode.</li> <li>• When key is removed, outside lever is locked.</li> <li>• Inside lever always free.</li> </ul>
		CL3780	Exit Latch	—	<ul style="list-style-type: none"> <li>• For twin communicating or exit doors where one side operation is required.</li> <li>• Also when space is limited between door and switch panel.</li> <li>• Deadlocking latchbolt.</li> <li>• One-lever operation.</li> <li>• Blank rose.</li> <li>• Should be used only where rooms have more than one entrance.</li> </ul>
		CL3750	Half Dummy Trim (Through-bolted)	—	<ul style="list-style-type: none"> <li>• Lever acts as pull only; no operation.</li> </ul>

# Options & Accessories

## CL3700

### Strikes




#### Curved Lip "T" Strike (Standard)

2-3/4" x 1-1/8" x 1-1/4" (70mm x 29mm x 32mm) lip to center

To order with lockset, see How to Order, page 6.


To order separately, specify 687F60 x Lip Length x Finish.



#### Dust Box for 2-3/4" (70mm) Curved Lip "T" Strike

To order with lockset, see How to Order, page 6.

To order separately, specify 687F94.




#### Full Lip Radius Corner

2-1/4" x 1-1/2" x 1" (57mm x 38mm x 25mm) lip to center

To order with lockset, see How to Order, page 6.


To order separately, specify 687F62 x 1-1/8" (29mm) x Finish.



#### Dust Box for 2-1/4" (57mm) Full Lip Radius and Square Corner Strikes

To order with lockset, see How to Order, page 6.

To order separately, specify 687F95.




#### ANSI Curved Lip

4-7/8" x 1-1/4" x 1-1/4" (124mm x 32mm x 32mm) lip to center

To order with lockset, see How to Order, page 6.


To order separately, specify 217L13 x Lip Length x Finish.



#### ANSI Wrought Strike Box

To order with lockset, see How to Order, page 6.

To order separately, specify 120F76-8.




#### Full Lip Square Corner

2-1/4" x 1-1/2" x 1" (57mm x 38mm x 25mm) lip to center

To order with lockset, see How to Order, page 6.

To order separately, specify 687F61 x Finish.

### Cylinders



#### Standard Cylinder

.509" (13mm) plug diameter conventional

.552" (14mm) plug diameter high security

.496" plug diameter Pyramid

Brass, 6-pin

**2 nickel silver keys**

Finishes: 606, 626

Conventional	6-Pin	(standard) 2000-037
Schlage® C Keyway	6-Pin	2400-037-C "O" bitted or keyed random
Pyramid High Security	7-Pin	2020-037
Pyramid Security	7-Pin	2027-037

To order optional cylinder with lockset, see How to Order, page 6.


To order cylinder separately, specify Part No. x Keyway x Finish (e.g., 2000-037 x L4 x 626).

### UL Firecup

#### Part No. 687F66

Supplied standard with all CL3700's.

Failure to use invalidates UL listing.




### Latches

To order optional latchbolt with lockset, see How to Order, page 6.

To order latchbolt separately, specify Part No. x Finish (e.g., 687F63 x 626).

All CL3700 latches are deadlocking.



Backset and Front Description	UL Latches
2-3/4" (70mm) Square Corner Front 2-1/4" x 1-1/8" (57mm x 29mm) faceplate	687F63
2-3/8" (60mm) Square Corner Front 2-1/4" x 1" (57mm x 25mm) faceplate	687F64
2-3/8" (60mm) 1/4" Round Corner Front 2-1/4" x 1" (57mm x 25mm) faceplate	687F65
1" (25mm) Latch Sleeve	687F71

### Screw Pack

#### Part No. 687F96

Supplied standard with wood-machine screws combination.

# How to Order/Quick Codes

## CL3700

### Ordering Examples

#### Stock Order

Quantity	Series/Function	Trim	Finish
100	CL3755	NZD	626

#### Contract/Detailed Order

Quantity	Keyset	Series/Function	Trim	Finish	Backset	Misc. Options	Keying
24	AA1	CL3755	NZD	626	B238	M17	CKC2

#### Cylinder and Keying

Description	Specify
Conventional 6-pin	(standard)
Less cylinder(s)	LC
Pyramid High Security Fixed Core	PHS
Pyramid Security Fixed Core	PS
0-bitted with 2 blank keys	(standard)
Keyed random	KR
Construction master keyed	CMK
Visual key control (VKC)	
No bitting or keyset stamping on keys	VKC0
Keys only	VKC1
Cylinders and keys (not for HS, CHS, PHS or PCHS)	VKC2
Cylinders only (not for HS, CHS, PHS or PCHS)	VKC3
Concealed key control (CKC)	
CKC cylinders with VKC keys	CKC2
CKC cylinders only (not for PHS, PCHS)	CKC3
Lockset furnished with Schlage® C Keyway cylinder	C
More than 2 keys	KY# (e.g., KY6)

#### Finishes

Description	Specify
BHMA 605 (US3) Bright Brass	605
BHMA 606 (US4) Satin Brass	606
BHMA 613 (US10B)* Oxidized Bronze, oil rubbed, available lacquered	613
BHMA 625 (US26) Bright Chromium Plated	625
BHMA 626 (US26D) Satin Chromium Plated	626
Zinc levers are plated to match BHMA finish.	

\* Simulated painted finish meeting ANSI standards for wear and durability.

\*\* Split finish only available on CL3720 - see page 4.

#### Strikes

Strike Type	Specify
Curved Lip "T" Strike	(standard)
ANSI Curved Lip	SA114
Full Lip 1/4" (6mm) Radius Corner	SFR114
Full Lip Square Corner	SF114

#### Door Thickness

Door Thickness	Specify
1-3/8" (35mm) - 1-3/4" (44mm)	(standard)

#### Where to find ordering information and quick codes

Finishes	Page 2
Handing	Page 7
Trim Designs	Page 3
Series/Functions	Page 4
Door Thickness	Page 6
Backsets	Page 7
Strikes	Page 5
Miscellaneous Options	Page 7
Cylinders and Keying	Page 6

# Quick Codes/Specifications

## CL3700

### Backset

Description	Specify
2-3/8" (60mm)	B238
2-3/4" (70mm)	(standard)

### Handing

Hand	Specify
Right Hand	RH
Left Hand	LH

\*Must specify hand for Frascati CL3755, 3759, 3780 and 3750.

### Miscellaneous Options

Description	Specify
Less cylinder, with tailpiece for Schlage® cylinder	M06
1-1/8" (29mm) latch front, square corners (standard with 2-3/4" (70mm) backset.) Available in 2-3/4" (70mm) backset only	Standard
1" (25mm) latch front, square corners (standard with 2-3/8" (60mm) backset). Available in 2-3/8" (60mm) backset only	Standard
1" (25mm) latch front, rounded corners. Available in 2-3/8" (60mm) backset only	M15
ANSI wrought strike box	M17
Dust box for 2-3/4" (70mm) strike	M77
Dust box for 2-1/4" (57mm) strike	M78

### Suggested Specification

Locksets shall be CL3700 Series Grade 2 Key-in-Lever Locksets.

Locks shall have an interlocking tubular chassis and latchbolt. Chassis mounting screws shall be accessible only when the inside lever and rose are removed.

The latchbolt shall have a 1/2" (13mm) throw and shall include a deadlocking feature to inhibit manipulation when the door is locked.

Locksets and latchbolts shall be reversible for ease of installation.

Locksets shall be adjustable for 1-3/8" (35mm) and 1-3/4" (44mm) door thickness. Levers shall have inside and outside lever return springs to prevent lever sag.

Lever handles shall be a minimum of 4-3/4" (121mm) in length and shall provide a minimum of 2-1/8" (54mm) clearance from surface of door to the inside of the lever at the midpoint.

Outside levers on keyed locksets shall be removable only when the designated key is in the cylinder.

Locksets shall be furnished with two nickel silver keys. All cylinder plugs shall be brass and furnished with 6-pin chambers for master keying capabilities.

Cylinders shall be easily changed by removing the lever without disassembling the lockset.

#### Certification:

UL 1-1/2 Hour Fire Rating  
ANSI A156.2 Series 4000, Grade 2  
ANSI A117.1 Accessibility Code  
All locksets shall carry a one-year warranty.



**ASSA ABLOY**

**In U.S.**

Corbin Russwin  
Architectural Hardware  
225 Episcopal Road  
Berlin, CT 06037  
Phone: 800-543-3658  
Fax: 800-447-6714  
[corbinrusswin.com](http://corbinrusswin.com)

**In Canada**

ASSA ABLOY Door  
Security Solutions Canada  
160 Four Valley Drive  
Vaughan, Ontario  
Canada L4K 4T9  
Phone: 800-461-3007  
Fax: 905-738-2478  
[www.assaabloy.ca](http://www.assaabloy.ca)

For more information regarding Corbin Russwin Locksets, Exit Devices, Door Controls and Key Systems, contact your authorized Corbin Russwin Distributor or Sales Representative.

Corbin Russwin and Design® is a registered trademark of Corbin Russwin, Inc., an ASSA ABLOY Group company. Other products' brand names may be trademarks or registered trademarks of their respective owners and are mentioned for reference purposes only. These materials are protected under US copyright laws. All contents current at time of publication. Corbin Russwin, Inc., an ASSA ABLOY Group Company, reserves the right to change availability of any item in this catalog, its design, construction, and/or its materials. Copyright © 2001, 2012 Corbin Russwin, Inc., an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Corbin Russwin, Inc. is prohibited.

ASSA ABLOY is the global leader in door opening solutions, dedicated to satisfying end-user needs for security, safety and convenience.



# CK4700 Series

Light/Medium Duty Knob Locksets



ASSA ABLOY, the global leader  
in door opening solutions

# Introduction

## CK4700



### Quality

The CK4700 series is a Grade 2 light/medium-duty knob lockset which provides an outstanding combination of value and performance. It is the ideal knob lockset for light commercial and heavy-duty residential applications such as interior offices, closets, multi-family housing, restaurants and retail complexes. The CK4700 series provides quality materials and performance.

### Vandal Resistance

CK4700 series locksets are available with Corbin Russwin's Pyramid patented\* security cylinder, the most secure locking system available. Pyramid is especially recommended for installations that require superior protection against picking and drilling. See the Key Systems catalog for additional information. (\* Patent No. 6, 125, 674)

### Key Advantages

- ANSI Grade 2 certification
- UL 1-1/2 hour fire rating
- Pyramid cylinders for increased security
- Interlocking tubular chassis and latchbolt

## Table of Contents

Introduction.....	2
Features.....	3
Functions.....	4
Trim Design.....	5
Options and Accessories.....	6
How to Order.....	8
Quick Codes.....	9
Specifications.....	10



### Features

#### Handing

Non-handed.

#### Door Thickness

1-3/8" (35mm) to 1-3/4" (44mm).

#### Lock Chassis

Die cast zinc for corrosion resistance.

#### Backset

2-3/4" (70mm) standard.

Optional: 2-3/8" (60mm). See Quick Codes, page 9.

#### Latches

1/2" (13mm) bolt projection.

#### Auxiliary Latchbolt

Deadlocking latchbolt prevents manipulation when door is closed.

#### Strike

T- Strike standard. Optional strikes, lip lengths and ANSI wrought strike box available; see Quick Codes, page 9.

#### Cylinder

Brass, 6-pin, L4 keyway, 0-bitted standard.

#### Keying Features Available

Master keying  
Construction master keying  
Visual key control  
Concealed key control  
High Security Pyramid

#### Keys

Two nickel silver standard.

#### Warranty

One-year limited.

### Certification/Compliance

#### ANSI

Meets A156.2 Series 4000, Grade 2.

#### UL/ULC


All locks listed for B Label Single doors.

UL symbol on latch front indicates listing.

Any retrofit or other field modification to a fire-rated opening can potentially impact the fire rating of the opening, and Corbin Russwin, Inc. makes no representations or warranties concerning what such impact may be in any specific situation. When retrofitting any portion of an existing fire rated opening, or specifying and installing a new fire-rated opening, please consult with a code specialist or local code official (Authority Having Jurisdiction) to ensure compliance with all applicable codes and ratings.







#### Finishes


BHMA 605	Bright Brass
BHMA 626	Satin Chromium Plated




# Functions


## CK4700

Outside	Inside	Series/Function	Type	ANSI No.	Function Description
		CK4710	Passage or Closet	F75	<ul style="list-style-type: none"> <li>• Deadlocking latchbolt by knob either side.</li> <li>• Both knobs always free.</li> </ul>
		CK4720	Privacy Bedroom or Bathroom	F76	<ul style="list-style-type: none"> <li>• Deadlocking latchbolt by knob either side.</li> <li>• Outside knob locked by button.</li> <li>• Outside knob unlocked by button inside, or by rotating inside knob.</li> <li>• Emergency release in outside knob.</li> <li>• Inside knob always free.</li> </ul>
		CK4751	Entrance or Office	F81	<ul style="list-style-type: none"> <li>• Deadlocking latchbolt by knob either side, except when button locks outside knob.</li> <li>• Rotating button locks outside knob, requiring key to unlock. Turning inside knob unlocks outside knob.</li> <li>• Rotating button the other way locks outside knob, requiring key to unlock. Turning inside knob unlocks outside knob only when button is rotated back to unlock.</li> <li>• Inside knob always free.</li> </ul>
		CK4755	Classroom	F84	<ul style="list-style-type: none"> <li>• Deadlocking latchbolt by knob either side, except when key outside locks outside knob.</li> <li>• Outside knob unlocked by key outside.</li> <li>• Inside knob always free.</li> </ul>
		CK4759	Storeroom or Public Restroom	F86	<ul style="list-style-type: none"> <li>• Deadlocking latchbolt by knob inside.</li> <li>• Key outside unlocks outside knob to retract latchbolt.</li> <li>• Knob retracts latchbolt.</li> <li>• Key is retained in the unlocked mode.</li> <li>• When key is removed, outside knob is locked.</li> <li>• Inside knob always free.</li> </ul>
		CK4750	Half Dummy Trim (Surface Mounted)	—	<ul style="list-style-type: none"> <li>• Knob acts as pull only; no operation.</li> <li>• Knob is rigid.</li> </ul>





**Global**



### **GWC**

Knob: Brass

Knob projection:  $\frac{2-9}{16}$ " (65mm)

Rose: Brass


Rose diameter:  $\frac{2-9}{16}$ " (65mm)

# Options and Accessories

## CK4700



### Latches

To order optional latchbolt with lockset, see Quick Codes, page 9.  
To order latchbolt separately, specify Part No. x Finish  
(e.g., 687F63 x 626).



Backset and Front Description			UL Latches
2-3/4" (70mm)	Square Corner Front	2-1/4" (57mm) x 1-1/8" (29mm) faceplate	687F63
2-3/8" (60mm)	Square Corner Front	2-1/4" (57mm) x 1" (25mm) faceplate	687F64
2-3/8" (60mm)	1/4" (6mm) Round Corner Front	2-1/4" (57mm) x 1" (25mm) faceplate	687F65
	1" (25mm) Latch Sleeve		687F71

**All CK4700 Latches are Deadlocking.**



### Cylinders

		<b>Standard Cylinder</b> .509" plug diameter conventional .496" plug diameter high security Brass, 6-pin 2 nickel silver keys Finishes: 606, 626
Conventional	6-Pin	(standard) (2000-037)
Pyramid High Security	7-pin	(2020-037)
Pyramid Security	7-pin	(2027-037)
Schlage® C Keyway	5-Pin	2400-037-C-5 "O" bitted or keyed random

To order optional cylinder with lockset, see Quick Codes, page 9.  
To order cylinder separately, specify Part No. x Keyway x Finish  
(e.g., 2000-037 x L4 x 626).

### UL Firecup

**Part No. 687F66**


Supplied standard with all CK4700's. Failure to use invalidates UL listing.

### Screw Pack

**Part No. 687F96**


Supplied standard with wood-machine screws combination.

### Strikes




#### Curved Lip "T" Strike

2-3/4" (70mm) x 1-1/8" (29mm) x  
1-1/4" (32mm) lip to center  
Supplied standard with lockset.  
To order separately, specify 586L19 x Lip  
Length x Finish.



#### ANSI Curved Lip

4-7/8" (124mm) x 1-1/4" (32mm) x  
1-1/4" (32mm) lip to center  
To order with lockset, specify SA114.  
To order separately, specify 217L13 x Lip  
Length x Finish.




#### Dust Box for 2-3/4" (70mm) Curved Lip "T" Strike

To order with lockset, specify M77.  
To order separately, specify 687F94 x  
Finish.




#### ANSI Wrought Strike Box

To order with lockset, specify M17.  
To order separately, specify 120F76-8.




#### Full Lip Radius Corner

2-1/4" (57mm) x 1-1/2" (38mm) x  
1" (25mm) lip to center  
To order with lockset, specify SFR114.  
To order separately, specify 687F62 x  
1-1/8" (29mm) x Finish.



#### Full Lip Square Corner

2-1/4" (57mm) x 1-1/2" (38mm) x 1" (25mm)  
lip to center  
To order with lockset, specify SF114.  
To order separately, specify 687F61 x Finish.



#### Dust Box for 2-1/4" (57mm) Full Lip Radius and Square Corner Strikes

To order with lockset, specify M78.  
To order separately, specify 687F95 x Finish.

# How to Order

## CK4700

### Ordering Examples

#### Stock Order

Quantity	Series/Function	Trim	Finish
100	CK4755	GWC	626

#### Where to find ordering information and quick codes

---

Handing	Page 3
Series/Function	Page 4
Trim Design	Page 5
Finish	Page 9
Door Thickness	Page 9
Backset	Page 9
Strike	Page 9
Miscellaneous Options	Page 9
Cylinders and Keying	Page 9

#### Contract/Detailed Order

Quantity	Keyset	Series/Function	Trim	Finish	Backset	Misc. Options	Keying
24	AA1	CK4755	GWC	626	B238	M17	CKC2



### Finishes

Description		Specify
BHMA 605 (US3)	Bright Brass	605
BHMA 626 (US26D)	Satin Chromium Plated	626

### Backset

Description	Specify
2-3/8" (60mm)	B238
2-3/4" (70mm)	(standard)

### Cylinder and Keying

Description	Specify
Conventional 6-pin	(standard)
Less cylinder	LC
0-bitted with 2 blank keys	(standard)
Keyed random	KR
Construction master keying (not available for Pyramid)	CMK
Pyramid High Security	PHS
Pyramid Security	PS
Visual Key Control (VKC)	
- No keying data stamped on key or cylinder	VKC0
- Keys only	VKC1
- Cylinders and keys (not for PHS)	VKC2
- Cylinders only (not for PHS)	VKC3
Concealed key control (CKC)	
- CKC cylinders with VKC keys	CKC2
- CKC cylinders only (not for PHS)	CKC3
2 keys per lock	(standard)
More than 2 keys	KY# (e.g., KY6)

### Door Thickness

Description	Specify
1-3/8" (35mm) - 1-3/4" (44mm)	(standard)

### Strike

Strike Type	Specify
ANSI Curved Lip	SA114
Curved Lip "T" Strike	(standard)
Full Lip 1/4" (6mm) Radius Corner	SFR114
Full Lip Square Corner	SF114

### Miscellaneous

Description	Specify
Less cylinder with tailpiece for Schlage® cylinder	M06
1-1/8" (29mm) latch front, square corners (standard with 2-3/4" (70mm) backset).	(standard)
1" (25mm) latch front, square corners (standard with 2-3/8" (60mm) backset). Available in 2-3/8" (60mm) backset only.	M14
1" (25mm) latch front, rounded corners. Available in 2-3/8" (60mm) backset only.	M15
Dust box for 2-3/4" (70mm) strike	M77
Dust box for 2-1/4" (57mm) strike	M78
ANSI wrought strike box	M17

# Specifications

## CK4700

Locksets shall be CK4700 Series Grade 2 Key-in-Knob Locksets.

Locks shall have an interlocking tubular chassis and latchbolt.

Locksets shall be adjustable for 1-3/8" (35mm) and 1-3/4" (44mm) door thickness. The latchbolt shall be adjustable to accommodate flat or beveled doors, shall have a 1/2" (13mm) throw and shall include a deadlocking feature to inhibit manipulation when door is closed.

Inside and outside knobs shall be of the same profile and projection for aesthetic continuity. The knob shall have a 2-9/16" (65mm) projection from face of door.

Locksets shall be furnished with two nickel silver keys. All cylinder plugs shall furnished with 6-pin chambers for master keying capabilities.

Cylinders shall be easily changed by removing the knob without disassembling the lockset.

**Certification:**

UL 1-1/2 Hour Fire Rating

ANSI A156.2 Series 4000, Grade 2

Locksets shall carry a one-year warranty.





**ASSA ABLOY**

**In U.S.**

Corbin Russwin  
Architectural Hardware  
225 Episcopal Road  
Berlin, CT 06037  
Phone: 800-543-3658  
Fax: 800-447-6714  
[corbinrusswin.com](http://corbinrusswin.com)

**In Canada**

ASSA ABLOY Door  
Security Solutions Canada  
160 Four Valley Drive  
Vaughan, Ontario  
Canada L4K 4T9  
Phone: 800-461-3007  
Fax: 905-738-2478  
[www.assaabloy.ca](http://www.assaabloy.ca)

For more information regarding Corbin Russwin Locksets, Exit Devices, Door Controls and Key Systems, contact your authorized Corbin Russwin Distributor or Sales Representative.

Corbin Russwin and Design® is a registered trademark of Corbin Russwin, Inc., an ASSA ABLOY Group company. Other products' brand names may be trademarks or registered trademarks of their respective owners and are mentioned for reference purposes only. These materials are protected under US copyright laws. All contents current at time of publication. Corbin Russwin, Inc., an ASSA ABLOY Group Company, reserves the right to change availability of any item in this catalog, its design, construction, and/or its materials. Copyright © 2001, 2011 Corbin Russwin, Inc., an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Corbin Russwin, Inc. is prohibited.

ASSA ABLOY is the global leader in door opening solutions, dedicated to satisfying end-user needs for security, safety and convenience.

**Corbin  
Russwin** 

**ASSA ABLOY**

## ED6000 Series

Crossbar Exit Devices



ASSA ABLOY, the global leader  
in door opening solutions



# Introduction

## ED6000

### ED6000 Series



#### Applications

Since patenting some of the first exit devices nearly a century ago, Corbin Russwin has met rigorous life safety and security requirements, while offering pleasing aesthetics and trouble-free operation. Designed for applications in high-use, high-abuse situations, ED6000 Crossbar Exit Devices can be teamed with a variety of Corbin Russwin trims to provide desired functions, styles and finishes in new construction and renovations, including:

- Schools and universities
- Health care facilities
- Government and municipal buildings
- Commercial and industrial
- Office and retail complexes
- Transportation facilities
- Hotels and conference centers
- Religious facilities

#### Advantages

- Meets ANSI Grade 1 requirements
- Heavy-duty construction
- Base metals (brass, bronze and stainless steel) for durability
- Easy-to-use crossbar operation for quick egress and ADA compliance
- Dogging standard on all panic listed devices
- Thru-bolted trims for strength and security
- Wide range of finishes, trims and styles to match other Corbin Russwin products
- Devices available to satisfy panic and fire opening requirements

### Table of Contents





Introduction.....	2
Applications and Listings.....	3
Rim Exit Features.....	5
Surface Vertical Rod Exit Features..	7
Rim/Surface Vertical Rod	
Trims and Functions .....	9
Fire-Rated Rim Exit Features .....	13
Fire-Rated Rim Trims	
and Functions .....	15
Mortise Exit Features.....	18
Mortise Trims and Functions .....	20
Concealed Vertical Rod	
Exit Features .....	24
Concealed Vertical Rod	
Trims and Functions.....	26
ED66900 ECE Applications.....	27
ECE Features.....	28
ECE Functions .....	29
Options and Accessories .....	30
Mullions.....	33
Cylinders.....	34
How to Order .....	35
Quick Codes .....	36
Helpful Terms .....	38
How to Specify .....	39

# Applications and Listings


ED6000

**UL** UL listed as fire exit hardware by Underwriters Laboratories Inc.

## Single Door

	Max. Door Opening	Fire Door Ratings					Application	
		A	B, D	C, E				
		3 Hr.	90 Min.	45 Min.	30 Min.	20 Min.		
<b>Rim</b>								
ED6200	4'*	Devices are panic listed only.					Surface applied; single point latching.	
ED6200A	4' x 7'2"	UL	UL	UL	UL	UL		
<b>Vertical Rod</b>								
ED6400	4' x 10'	Devices are panic listed only.					Surface applied; two point latching.	
ED6400A	4' x 7'2"	Fire ratings do not apply for single door applications.						
<b>Mortise</b>								
ED6600	4'*	Devices are panic listed only.					Mortised in door; two point latching.	
ED6600A	4' x 7'2"	UL	UL	UL	UL	UL		
<b>Concealed Vertical Rod</b>								
ED6800	4' x 10'8"	Devices are panic listed only.					Rods concealed in door; two point latching.	
ED6800A	4' x 7'2"	Fire ratings do not apply for single door applications.						

## Pair of Doors with Removable Mullion







	Max. Door Opening	Fire Door Ratings					Application	
		A	B, D	C, E				
		3 Hr.	90 Min.	45 Min.	30 Min.	20 Min.		
<b>Rim x Rim</b>								
ED6200 x ED6200 x 507	8' x 7'2"	Devices are panic listed only.					2 independent, active doors with removable mullion.	
ED6200 x ED6200 x 510	8' x 10'	Fire ratings do not apply.						
ED6200A x ED6200A x 507	8' x 7'2"	UL	UL	UL	UL	UL		

\*UL does not set a door height limitation on panic applications.

# Applications and Listings

## ED6000

### Pair of Doors

	Max. Door Opening	Fire Door Ratings					Application	
		A	B, D	C, E				
		3 Hr.	90 Min.	45 Min.	30 Min.	20 Min.		
<b>Vertical Rod (Swinging in the Same Direction)</b>								
ED6400 x ED6400	8'*	Devices are panic listed only.					2 independent doors with 2 point latching – overlapping astragal not required.	
ED6400A x ED6400A	8' x 7'2"	—	UL	UL	UL	UL		
<b>Vertical Rod (Swinging in Opposite Directions)</b>								
ED6400 x ED6400	8'*	Devices are panic listed only.					2 independent doors with 2 point latching – overlapping astragal required for 3 hour openings.	
ED6400A x ED6400A	8' x 7'2"	UL	UL	UL	UL	UL		
<b>Vertical Rod x Mortise</b>								
ED6400 x ED6600	8'*	Devices are panic listed only.					Overlapping astragal required for 3 hour openings. Coordinator required with standard strike.	
ED6400A x ED6600A	8' x 7'2"	UL	UL	UL	UL	UL		
ED6400A x ED6600A x Open back strike	8' x 7'2"	—	UL	UL	UL	UL		
<b>Vertical Rod x Rim</b>								
ED6400 x ED6200 x S02	8'*	Devices are panic listed only.					Non-prepped doors only; S02 strike required on inactive door; coordinator recommended.	
<b>Concealed Vertical Rod (Swinging in the Same Direction)</b>								
ED6800 x ED6800	8'*	Devices are panic listed only.					2 independent doors with 2 point latching – overlapping astragal not required.	
ED6800A x ED6800A	8' x 7'2"	—	UL	UL	UL	UL		
<b>Concealed Vertical Rod (Swinging in Opposite Directions)</b>								
ED6800 x ED6800	8'*	Devices are panic listed only.					2 independent doors with 2 point latching – overlapping astragal required for 3 hour openings.	
ED6800A x ED6800A	8' x 7'2"	UL	UL	UL	UL	UL		

\*UL does not set a door height limitation on panic applications.





## ED6200 Panic Listed Rim Exit Device

### Features

#### Handing

Field reversible; specify hand.

#### Bar Length

Easily field cut to size.

Standard: 36" (914mm) bar fits up to 36" (914mm) door.

Optional: 48" (1219mm) bar fits up to 48" (1219mm) door; specify W048.

#### Door Thickness

1-3/4" (44mm) standard.

Optional: 2" (51mm); specify D200.

Optional: 2-1/4" (57mm); specify D214.

#### Backset

2-5/8" for 1/2" stop, 2-3/4" for 5/8" stop. (Backset changes when mullion is used.)

#### Stile

Minimum width with 1/2" stop and standard strike 4" (102mm).

#### Latchbolt

3/4" (19mm) pivoted.

#### Materials

Brass, bronze or stainless steel.

#### Cases

Heavy wrought, 7-1/4" (184mm) x 2-9/16" (65mm).

#### Projection

5-3/4" (146mm); 4-1/2" (114mm) depressed.

#### Crossbar

Standard: 13/16" (1mm) x 1-3/8" (35mm) oval seamless tubing.

Optional: reinforced crossbar or stainless steel crossbar; see Quick Codes, page 36.

#### Dogging

Standard on ED6200 devices.

Optional: less dogging; specify M51.

#### Fasteners

Standard: machine screws.

Optional: sex nuts and bolts or spanner head screws; specify M54.

#### Strike:

See Options and Accessories, page 30.

#### Removable Mullion

See Mullions, page 33.

#### Functions and Trims

Thru-bolted lever, knob, pull and thumbpiece trims available with wide range of functions; see Trims and Functions, page 9.

#### Cylinders

Cylinder not included unless specified. See How to Order, page 34.

#### Applications and Listings

See page 3.

#### Warranty

One-year limited.

### Certification/Compliance

#### ANSI

Meets A156.3, Grade 1.

Meets A117.1 Accessibility Code.

#### C-UL US

All devices listed for safety as panic hardware; devices comply with UL 305 standards for panic hardware. UL symbol on active case cover indicates listing.

#### California State Reference Code

This product has been approved by the California State Fire Marshal pursuant to section 13144.1 of the California Health and Safety Code.

#### NFPA

All exit devices comply with NFPA 101 Life Safety Code.

#### ADA

Exit devices, lever trims and pulls comply with Americans with Disabilities Act.


### Finishes

BHMA 605	Bright Brass	
BHMA 606	Satin Brass	
BHMA 611	Bright Bronze	
BHMA 612	Satin Bronze	
BHMA 613	Oxidized Bronze, oil rubbed, available lacquered	
BHMA 618	Bright Nickel Plated	
BHMA 619	Satin Nickel Plated	
BHMA 622	Flat Black Coated	
BHMA 625	Bright Chromium Plated	
BHMA 626	Satin Chromium Plated	
626C	Satin Chromium Plated with MicroShield®	
BHMA 629	Bright Stainless Steel	
BHMA 630	Satin Stainless Steel	
630C	Satin Stainless Steel with MicroShield®	
BHMA 722	Black oxidized bronze, oil rubbed	

# Rim Exit Features

ED6000

## ED6200 Rim Exit Device



# Surface Vertical Rod Exit Features

ED6000

## ED6400 Panic Listed Vertical Rod Exit Device ED6400A 3-Hour Fire Listed Vertical Rod Exit Device

### Features

#### Handing

Device handed but easily field reversible; specify hand.

#### Bar Length

Easily field cut to size.

Standard: 36" (914mm) bar fits up to 36" (762mm-914mm) door.

Optional: 48" (1219mm) bar fits up to 48" (1219mm) door; specify W048.

#### Door Thickness

1-3/4" (44mm) standard.

Optional: 2" (51mm); specify D200.

Optional: 2-1/4" (57mm); specify D214.

#### Backset

2-3/4" (70mm).

#### Stile

Minimum width 4-1/8" (105mm).

#### Door Height

All top rods easily field cut to size.

Standard on ED6400 devices; top rod for doors up to 7'6".

Optional on ED6400 devices; top rod for doors up to 10'; see How to Order, page 35.

Standard on ED6400A devices; top rod for 7'2" door.

#### Latchbolt

ED6400 devices:

Top: 5/8" throw.

Bottom: 3/4" throw; acts independently, allowing top latch to remain engaged even when bottom latch is not projected.

ED6400A devices:

Top: 3/4" steel, jamb mounted; projects into pusher on device.

Bottom: 3/4" throw steel.

#### Latchbolt Operation

Standard on ED6400 and ED6400A devices: latchbolts held in retracted position until door closes.

Optional on ED6400 devices: free-latching latchbolts; see How to Order, page 35.

#### Vertical Rods

Inverted U-shaped rectangular.

#### Materials

Brass, bronze or stainless steel.

#### Cases

Heavy wrought, 7-1/4" (184mm) x 2-9/16" (65mm).

#### Crossbar

Standard: 13/16" (1mm) x 1-3/8" (35mm) oval seamless tubing.

Optional: reinforced crossbar or stainless steel crossbar; see Quick Codes, page 36.

#### Dogging

Standard on ED6400 devices.

Optional: less dogging; specify M51.

Dogging not available on ED6400A devices.

#### Projection

5-3/4" (146mm); 4-1/4" (108mm) depressed.

#### Fasteners

Standard on ED6400 devices: machine screws.

Optional on ED6400 devices: sex nuts and bolts; specify M54.

Standard on ED6400A devices; sex nuts and bolts.

Optional on ED6400 and ED6400A devices; spanner head screws; specify M02.

#### Strike

See Options and Accessories, page 31.

#### Functions and Trims

Thru-bolted lever, knob, pull and thumbpiece trims available with wide range of functions; see Trims and Functions, page 9.

#### Cylinders

Cylinder not included unless specified. See How to Order, page 34.

#### Applications and Listings

See page 3.

#### Warranty

One-year limited.

### Certification/Compliance

#### ANSI

Meets A156.3, Grade 1.

#### C-UL US

All devices listed for safety as panic hardware; devices comply with UL 305 standards for panic hardware. 3-hour fire-rated devices listed as fire exit hardware for A label and lesser class 8' x 7'2" double doors. UL symbol on active head indicates listing.

Any retrofit or other field modification to a fire-rated opening can potentially impact the fire rating of the opening, and Corbin Russwin, Inc. makes no representations or warranties concerning what such impact may be in any specific situation. When retrofitting any portion of an existing fire-rated opening, or specifying and installing a new fire-rated opening, please consult with a code specialist or local code official (Authority Having Jurisdiction) to ensure compliance with all applicable codes and ratings.

#### California State Reference Code

This product has been approved by the California State Fire Marshal pursuant to section 13144.1 of the California Health and Safety Code.



#### NFPA

All exit devices comply with NFPA 101 Life Safety Code. All fire-rated devices comply with NFPA 80 Fire Doors and Windows.

#### ADA

Lever trims and pulls comply with Americans with Disabilities Act.

#### Finishes


BHMA 605	Bright Brass
BHMA 606	Satin Brass
BHMA 611	Bright Bronze
BHMA 612	Satin Bronze
BHMA 613	Oxidized Bronze, oil rubbed, available lacquered
BHMA 618	Bright Nickel Plated
BHMA 619	Satin Nickel Plated
BHMA 622	Flat Black Coated
BHMA 625	Bright Chromium Plated
BHMA 626	Satin Chromium Plated
626C	Satin Chromium Plated with MicroShield® 
BHMA 629	Bright Stainless Steel
BHMA 630	Satin Stainless Steel
630C	Satin Stainless Steel with MicroShield® 
BHMA 722	Black oxidized bronze, oil rubbed

# Surface Vertical Rod Exit Features

ED6000

## ED6400 Vertical Rod Surface Exit Device

## ED6400A Vertical Rod Surface Exit Device



# Rim/SVR Trims and Functions







ED6000

## Device Only

Rim Exit Device	ANSI Type	Type	ANSI No.	Function Description
ED6200	2	Exit Only	01	Exit only; no trim. (Accepts all trims listed on pages 9-12).
Vertical Rod Exit Device	ANSI Type	Type	ANSI No.	Function Description
ED6400	2	Exit Only	01	Exit only; no trim.
ED6400A	2	Exit Only	01	3-hour fire-rated exit only; no trim.










## Device with Trim

Vertical Rod Exit Device	Accepts Trim/Function			Function Description (See Trim Designs Below)
	ANSI Type	Type	ANSI No.	
ED6410	2	Passage (10)	—	- Free at all times.
ED6410A	2	Passage (10)	—	- 3-hour fire-rated; free at all times.
ED6450	2	Dummy (50)	02	- Always rigid.
ED6450A	2	Dummy (50)	02	- 3-hour fire-rated; always rigid.
ED6410	2	Classroom (55)	05/08	- Free at all times, except when locked by key.
ED6410A	2	Classroom (55)	05/08	- 3-hour fire-rated; free at all times, except when locked by key.
ED6457	2	Classroom (55)	03/04/06	- Free only when key is turned. Key removable only when locked. - Not available fire-rated.
ED6458	2	Latch Hold-Back x Nighlatch Trim (57)	04/06	- Always inactive. Locked except when latch is held in retracted position by key. (Outside cylinder dogging) - Not available on fire-rated devices.

Pull Trim Design		Trim/Function					
		Passage ANSI No. 14	Dummy ANSI No. 02	Classroom ANSI No. 08	Nighlatch ANSI No. 03		
	<b>Armstrong A3</b> Lever: Cast Escutcheon: Cast Cylinder: Rim			A310	A350	A355	A357
	<b>Citation C2</b> Lever: Cast Escutcheon: Cast Cylinder: Rim			C210	C250	C255	C257













# Rim/SVR Trims and Functions

## ED6000

Pull Trim Design				Trim/Function			
				Passage ANSI No. 14	Dummy ANSI No. 02	Classroom ANSI No. 08	Nightlatch ANSI No. 03/04
	<p><b>Dirke D2</b></p> <p>Lever: Cast Escutcheon: Cast Cylinder: Rim</p>			D210	D250	D255	D257
	<p><b>Essex E2</b></p> <p>Lever: Cast Escutcheon: Cast Cylinder: Rim</p>			E210	E250	E255	E257
	<p><b>Lustra L2</b></p> <p>Lever: Cast Escutcheon: Cast Cylinder: Rim</p>			L210	L250	L255	L257
	<p><b>Newport N3</b></p> <p>Lever: Cast Escutcheon: Cast Cylinder: Rim</p>			N310	N350	N355	N357
	<p><b>Regis R2</b></p> <p>Lever: Cast Escutcheon: Cast Cylinder: Rim</p>			R210	R250	R255	R257
	<p><b>Princeton PR2</b></p> <p>Lever: Cast Escutcheon: Cast Cylinder: Rim</p>			PR210	PR250	PR255	PR257

# Rim/SVR Trims and Functions







ED6000

Pull Trim Design	Trim/Function				
	Passage ANSI No. 14	Dummy ANSI No. 02	Classroom ANSI No. 08	Nightlatch ANSI No. 03/04	
 <p><b>Belmont B3</b> Knob: Wrought reinforced Escutcheon: Cast Cylinder: Rim</p>		B310	B350	B355	B357*
 <p><b>Global G4</b> Knob: Wrought reinforced Escutcheon: Cast Cylinder: Rim</p>		G410	G450	G455	G457*
 <p><b>D Grip T3</b> Grip: Extruded Escutcheon: Wrought Cylinder: Rim</p>		T310	T350	T355	T357*
 <p><b>Round Grip T4</b> Grip: Extruded Escutcheon: Wrought Cylinder: Rim</p>		T410	T450	T455	T457*
 <p><b>D Grip Sectional T5</b> Grip: Extruded Cylinder: Rim</p>		T510	T550	T555	T557*
 <p><b>Round Grip Sectional T6</b> Grip: Extruded Cylinder: Rim</p>		T610	T650	T655	T657*

\*When used with ED6458 device, provides latch hold-back for ANSI No. 04 function.

# Offset Pull Trims

ED6000

Offset Pull Trim: P12, P13, P14*			
	<p><b>Offset Pull P12</b> Clearance: 2-1/2 "</p>		<p>Specify Part Number, 716F50M x Finish<sup>1</sup></p>
	<p><b>Offset Pull P13</b> Clearance: 2-1/2 "</p>		<p>Specify Part Number, 716F51M x Finish<sup>1</sup></p>
	<p><b>Offset Pull P14</b> Clearance: 2-1/2 "</p>		<p>Specify Part Number, 716F52M x Finish<sup>1</sup></p>

1. Available in 605, 606, 612, 613, 626, 629 and 630 finishes.

\*Available on 1-3/4" thick doors only





## ED6200A 3-Hour Fire Listed Rim Exit Device

### Features

#### Handing

Handed; specify hand.

#### Bar Length

Easily field cut to size.

Standard: 36" (914mm) bar fits up to 36" (762mm-914mm) door.

Optional: 48" (1219mm) bar fits up to 48" (1219mm) door; specify W048.

#### Door Thickness

1-3/4" (44mm) standard.

Optional: 2" (51mm); specify D200.

Optional: 2-1/4" (57mm); specify D214.

#### Backset

2-3/4" (70mm) with 6/8" (19mm) stop. (Backset changes when mullion is used.)

#### Stile

Minimum width with 5/8" stop and standard strike: 4-1/8" (105mm).

#### Latchbolt

3/4" (19mm) throw stainless steel, with stainless steel deadlocking plunger.

#### Materials

Brass, bronze or stainless steel.

#### Cases

Heavy wrought, 8-3/8" (213mm) x 2-5/8" (67mm).

#### Crossbar

Standard: 13/16" (1mm) x 1-3/8" (35mm) oval seamless tubing.

Optional: reinforced crossbar or stainless steel crossbar; see Quick Codes, page 36.

#### Dogging

Not available.

#### Projection

5-3/4" (146mm); 3" (76mm) depressed.

#### Fasteners

Sex nuts and bolts standard.

Optional: spanner head screws; specify M02.

#### Strike

See Options and Accessories, page 30.

#### Removable Mullion

See Mullions, page 33.

### Functions and Trims

Thru-bolted lever, knob, pull and thumbpiece trims available with wide range of functions; see Trims and Functions, page 15.

### Cylinders

Cylinder not included unless specified. See How to Order, page 34.

### Applications and Listings

See page 3.

### Warranty

One-year limited.

### Certification/Compliance

#### ANSI

Meets A156.3, Grade 1.

Meets A117.1 Accessibility Code.

#### C-UL US

All devices listed for safety as panic hardware; devices comply with UL 305 standards for panic hardware. 3-hour fire-rated devices listed as fire exit hardware for A label and lesser class 8' x 7'2" double doors. UL symbol on active head indicates listing.

Any retrofit or other field modification to a fire-rated opening can potentially impact the fire rating of the opening, and Corbin Russwin, Inc. makes no representations or warranties concerning what such impact may be in any specific situation. When retrofitting any portion of an existing fire-rated opening, or specifying and installing a new fire-rated opening, please consult with a code specialist or local code official (Authority Having Jurisdiction) to ensure compliance with all applicable codes and ratings.

#### California State Reference Code

This product has been approved by the California State Fire Marshal pursuant to section 13144.1 of the California Health and Safety Code.



### NFPA

All exit devices comply with NFPA 101 Life Safety Code. All fire-rated devices comply with NFPA 80 Fire Doors and Windows.

### ADA

Exit devices, lever trims and pulls comply with Americans with Disabilities Act.


### Finishes

BHMA 605	Bright Brass
BHMA 606	Satin Brass
BHMA 611	Bright Bronze
BHMA 612	Satin Bronze
BHMA 613	Oxidized Bronze, oil rubbed, available lacquered
BHMA 618	Bright Nickel Plated
BHMA 619	Satin Nickel Plated
BHMA 622	Flat Black Coated
BHMA 625	Bright Chromium Plated
BHMA 626	Satin Chromium Plated
626C	Satin Chromium Plated with MicroShield® 
BHMA 629	Bright Stainless Steel
BHMA 630	Satin Stainless Steel
630C	Satin Stainless Steel with MicroShield® 
BHMA 722	Black oxidized bronze, oil rubbed

# Fire-Rated Rim Exit Features

ED6000

## ED6200A Rim Exit Device



# Fire-Rated Rim Trims and Functions






ED6000

## Device Only

Rim Exit Device	ANSI Type	Type	ANSI No.	Function Description
ED6200A	1	Exit Only	01	3-hour fire-rated exit only; no trim. (Accepts all trims listed on pages 15-17.)












## Device with Trim

Rim Exit Device	ANSI Type	Accepts Trim/Function		Function Description (See Trim Designs Below)
		Type	ANSI No.	
ED6200A	1	Passage (10)	—	- 3-hour fire-rated; free at all times.
ED6200A	1	Dummy (50)	—	- 3-hour fire-rated; always free wheeling.
ED6200A	1	Classroom (55)	05/08	- 3-hour fire-rated; free at all times, except when locked by key.
ED6257A	1	Nightlatch (57)	03/04/06/06	- 3-hour fire-rated; always rigid. Entrance by trim when latchbolt is retracted by key. Key removable only when locked.

Pull Trim Design		Trim/Function					
		Passage	Dummy ANSI No. F02	Classroom ANSI No. F08	Nightlatch ANSI No. F03/F04/F06		
	<b>Armstrong A4</b> Lever: Cast Escutcheon: Cast Cylinder: Rim			A410	A450	A455	A457
	<b>Citation C3</b> Lever: Cast Escutcheon: Cast Cylinder: Rim			C310	C350	C355	C357













# Fire-Rated Rim Trims and Functions

## ED6000

Pull Trim Design				Trim/Function			
				Passage	Dummy ANSI No. F02	Classroom ANSI No. F08	Nightlatch ANSI No. F03/F04/F06
	<b>Dirke D3</b> Lever: Cast Escutcheon: Cast Cylinder: Rim			D310	D350	D355	D357
	<b>Essex E3</b> Lever: Cast Escutcheon: Cast Cylinder: Rim			E310	E350	E355	E357
	<b>Lustra L3</b> Lever: Cast Escutcheon: Cast Cylinder: Rim			L310	L350	L355	L357
	<b>Newport N4</b> Lever: Cast Escutcheon: Cast Cylinder: Rim			N410	N450	N455	N457
	<b>Regis R3</b> Lever: Cast Escutcheon: Cast Cylinder: Rim			R310	R350	R355	R357
	<b>Princeton PR3</b> Lever: Cast Escutcheon: Cast Cylinder: Rim			PR310	PR350	PR355	PR357

# Fire-Rated Rim Trims and Functions

ED6000

Pull Trim Design	Trim/Function				
	Passage	Dummy ANSI No. F02	Classroom ANSI No. F08	Nightlatch ANSI No. F03/F04/F06	
 <p><b>Belmont B4</b> Knob: Wrought reinforced Escutcheon: Cast Cylinder: Rim</p>		B410	B450	B455	B457
 <p><b>Global G5</b> Knob: Wrought reinforced Escutcheon: Cast Cylinder: Rim</p>		G510	G550	G555	G557
 <p><b>D Grip T7</b> Grip: Extruded Escutcheon: Wrought Cylinder: Rim</p>		T710	T750	T755	T757
 <p><b>Round Grip T8</b> Grip: Extruded Escutcheon: Wrought Cylinder: Rim</p>		T810	T850	T855	T857
 <p><b>D Grip Sectional T9</b> Grip: Extruded Cylinder: Rim</p>		T910	T950	T955	T957
 <p><b>Round Grip Sectional T10</b> Grip: Extruded Cylinder: Rim</p>		T1010	T1050	T1055	T1057

# Mortise Exit Features

## ED6000

### ED6600 Panic-Listed Mortise Exit Device ED6600A 3-Hour Fire-Listed Mortise Exit Device



#### Features

##### Handing

Device handed but easily field reversible; specify hand. Strike is not field reversible.

##### Bar Length

Easily field cut to size.  
Standard: 36" (914mm) bar fits up to 36" (762mm-914mm) door.  
Optional: 48" (1219mm) bar fits up to 48" (1219mm) door; specify W048.

##### Door Thickness

1-3/4" (44mm) standard.  
Optional: 2" (51mm); specify D200.  
Optional: 2-1/4" (57mm); specify D214.

##### Backset

2-3/4" (70mm).

##### Stile

Minimum width 5" (127mm).

##### Projection

5-3/4" (146mm); 4-1/2" (114mm) depressed.

##### Latchbolt

Brass, 3/4" (19mm) throw.

##### Auxiliary Latch

Brass.

##### Front

8" x 1-1/4" (203mm x 32mm) heavy gauge steel.

Accommodates flat doors and doors beveled 1/8" (3mm) in 2" (51mm).

##### Latch Hold-Back

On ED6600 devices with keyed function trim, latchbolt may be held in retracted position by pushing in latchbolt and turning key.

Not available on ED6600A devices.

##### Materials

Brass, bronze or stainless steel.

##### Cases

Heavy wrought, 7-1/4" (184mm) x 2-9/16" (65mm).

##### Crossbar

Standard: 13/16" (1mm) x 1-3/8" (35mm) oval seamless tubing.

Optional: reinforced crossbar or stainless steel crossbar; see Quick Codes, page 36.

##### Dogging

Standard on ED6600 devices.  
Optional less dogging; specify M51.  
Dogging not available on ED6600A devices.

##### Fasteners

Standard on ED6600 devices: machine screws.  
Optional on ED6600 devices: sex nuts and bolts; specify M54.  
Standard on ED6600A devices; sex nuts and bolts.

Optional on ED6600 and ED6600A devices; spanner head screws; specify M02.

##### Strike

See Options and Accessories, page 32.

##### Functions and Trims

Thru-bolted lever, knob, pull and thumbpiece trims available with wide range of functions; see Trims and Functions, page 20.

##### Cylinders

Cylinder not included unless specified. See How to Order, page 34.

##### Applications and Listings

See page 3.

##### Warranty

One-year limited.

#### Certification/Compliance

##### ANSI

Meets A156.3, Grade 1.  
Meets A117.1 Accessibility Code.

##### C-UL US

All devices listed for safety as panic hardware; devices comply with UL 305 standards for panic hardware. 3-hour fire-rated devices listed as fire exit hardware for A label and lesser class 4'x7'2" double doors. UL symbol on active head indicates listing.

Any retrofit or other field modification to a fire-rated opening can potentially impact the fire rating of the opening, and Corbin Russwin, Inc. makes no representations or warranties concerning what such impact may be in any specific situation. When retrofitting any portion of an existing fire-rated opening, or specifying

and installing a new fire-rated opening, please consult with a code specialist or local code official (Authority Having Jurisdiction) to ensure compliance with all applicable codes and ratings.

##### California State Reference Code

This product has been approved by the California State Fire Marshal pursuant to section 13144.1 of the California Health and Safety Code.



##### NFPA

All exit devices comply with NFPA 101 Life Safety Code. All fire-rated devices comply with NFPA 80 Fire Doors and Windows.


##### ADA

Exit devices, lever trims and pulls comply with Americans with Disabilities Act.

#### Finishes

BHMA 605	Bright Brass
BHMA 606	Satin Brass
BHMA 611	Bright Bronze
BHMA 612	Satin Bronze
BHMA 613	Oxidized Bronze, oil rubbed, available lacquered
BHMA 618	Bright Nickel Plated
BHMA 619	Satin Nickel Plated
BHMA 622	Flat Black Coated
BHMA 625	Bright Chromium Plated
BHMA 626	Satin Chromium Plated
626C	Satin Chromium Plated with MicroShield® 
BHMA 629	Bright Stainless Steel
BHMA 630	Satin Stainless Steel
630C	Satin Stainless Steel with MicroShield® 
BHMA 722	Black oxidized bronze, oil rubbed

### ED6600 and ED6600A Mortise Exit Devices









# Mortise Trims and Functions

## ED6000

Mortise Exit Device	ANSI Type	Accepts Trim/Function		Function Description (See Trim Designs Below)
		Type	ANSI No.	
ED6600	3	Exit Only	F01	- Exit only; no trim. (Accepts all trims listed on pages 20-23.)
ED6600A	3	Exit Only	F01	- 3-hour fire-rated exit only; no trim. (Accepts all trims listed on pages 20-22.)
For Passage, Dummy, Classroom and Nightlatch functions, see Trim Designs below.		Passage (10)	—	- Free at all times.
		Dummy (50)	F02	- Always free wheeling.
		Classroom (55)	F05/F08	- Free at all times, except when locked by key.
		Nightlatch (57)	F03	- Entrance by trim when latchbolt is retracted by key. Key removable only when locked.
ED6600	—	Latch hold back	—	- Latchbolt held in retracted position by pushing in latchbolt and turning key.



















### Device with Trim

Pull Trim Design		Trim/Function					
		Passage	Dummy ANSI No. F02	Classroom ANSI No. F05/F08	Nightlatch ANSI No. F03		
	<b>Armstrong A4M</b> Lever: Cast Escutcheon: Cast Cylinder: 1-3/4" Mortise A02 Cam			A4M10	A4M50	A4M55	A4M57
	<b>Citation C3M</b> Lever: Cast Escutcheon: Cast Cylinder: 1-3/4" Mortise A02 Cam			C3M10	C3M50	C3M55	C3M57






# Mortise Trims and Functions

ED6000

Pull Trim Design				Trim/Function			
				Passage	Dummy ANSI No. F02	Classroom ANSI No. F05/F08	Nightlatch ANSI No. F03
	<p><b>Dirke D3M</b></p> <p>Lever: Cast Escutcheon: Cast Cylinder: 1-3/4" Mortise A02 Cam</p> 		D3M10	D3M50	D3M55	D3M57	
	<p><b>Essex E3M</b></p> <p>Lever: Cast Escutcheon: Cast Cylinder: 1-3/4" Mortise A02 Cam</p> 		E3M10	E3M50	E3M55	E3M57	
	<p><b>Lustra L3M</b></p> <p>Lever: Cast Escutcheon: Cast Cylinder: 1-3/4" Mortise A02 Cam</p> 		L3M10	L3M50	L3M55	L3M57	
	<p><b>Newport N4M</b></p> <p>Lever: Cast Escutcheon: Cast Cylinder: 1-3/4" Mortise A02 Cam</p> 		N4M10	N4M50	N4M55	N4M57	
	<p><b>Regis R3M</b></p> <p>Lever: Cast Escutcheon: Cast Cylinder: 1-3/4" Mortise A02 Cam</p> 		R3M10	R3M50	R3M55	R3M57	
	<p><b>Princeton PR3M</b></p> <p>Lever: Cast Escutcheon: Cast Cylinder: 1-3/4" Mortise A02 Cam</p> 		PR3M10	PR3M50	PR3M55	PR3M57	







# Mortise Trims and Functions

## ED6000

Knob or Thumbpiece Trim Design	Trim/Function				
	Passage	Dummy ANSI No. F02	Classroom ANSI No. F05/F08	Nightlatch ANSI No. F03	
 <p><b>Belmont B4M</b> Knob: Wrought reinforced Escutcheon: Cast Cylinder: 1-1/2" Mortise A02 Cam</p>		B4M10	B4M50	B4M55	B4M57
 <p><b>Global G5M</b> Knob: Wrought reinforced Escutcheon: Cast Cylinder: 1-1/2" Mortise A02 Cam</p>		G5M10	G5M50	G5M55	G5M57
 <p><b>D Grip T7M</b> Grip: Extruded Escutcheon: Wrought Cylinder: 1-1/4" Mortise A02 Cam</p>		T7M10	T7M50	T7M55	T7M57
 <p><b>Round Grip T8M</b> Grip: Extruded Escutcheon: Wrought Cylinder: 1-1/4" Mortise A02 Cam</p>		T8M10	T8M50	T8M55	T8M57
 <p><b>D Grip Sectional T9M</b> Grip: Extruded Cylinder: 1-1/4" Mortise A02 Cam</p>		T9M10	T9M50	T9M55	T9M57
 <p><b>Round Grip Sectional T10M</b> Grip: Extruded Cylinder: 1-1/4" Mortise A02 Cam</p>		T10M10	T10M50	T10M55	T10M57

# Offset Pull Trims

ED6000

Offset Pull Trim: P12, P13, P14*			
	<p><b>Offset Pull P12</b> Clearance: 2-1/2 "</p>		<p>Specify Part Number, 716F50M x Finish<sup>1</sup></p>
	<p><b>Offset Pull P13</b> Clearance: 2-1/2 "</p>		<p>Specify Part Number, 716F51M x Finish<sup>1</sup></p>
	<p><b>Offset Pull P14</b> Clearance: 2-1/2 "</p>		<p>Specify Part Number, 716F52M x Finish<sup>1</sup></p>

1. Available in 605, 606, 612, 613, 626, 629 and 630 finishes.  
\*Available on 1-3/4" thick doors only.

# Concealed Vertical Rod Exit Features

## ED6000

### ED6800 Panic-Listed Concealed Vertical Rod Exit Device



### ED6800A 3-Hour Fire-Listed Concealed Vertical Rod Exit Device

For use with metal doors only.

#### Features

##### Handing

Field reversible; specify hand.

##### Bar length

Easily field cut to size.

Standard 36" bar fits doors up to 36" (914mm).

Optional 48" bar fits up to 48" (1219mm) doors; specify W048.

##### Door Thickness

1-3/4" (44mm) only (properly reinforced doors).

##### Backset

2-3/4" (70mm).

##### Stile

Minimum width 4-1/8" (108mm).

##### Door Height

All top rods easily field cut to size.

Standard on ED6800 devices: top rod for doors up to 8'6" .

Optional on ED6800 devices: top rod for doors up to 10' x 8"; see Quick Codes, page 36.

Standard on ED6800A devices: top rod for 7'2" door.

##### Projection

5-3/4" (150mm); 4-1/2" (114mm) depressed.

##### Latchbolts

Top: 3/4" (19mm) pivoted and deadlocking.

Bottom: 13/16" (20mm) throw rounded steel.

##### Rods

Top: 3/8" (10mm) solid steel.

Bottom: 1/2" (13mm) O.D. steel tubing.

##### Materials

Brass, bronze or stainless steel.

##### Cases

Heavy wrought, 7-1/4" x 2-9/16" (184mm x 65mm)

##### Crossbar

Standard: 13/16" x 1-3/8" (20mm x 35mm) oval seamless tubing.

Optional: reinforced crossbar or stainless steel crossbar; see Quick Codes, page 36.

##### Dogging

Standard on ED6800 devices.

Optional on ED6800 devices: less dogging, specify M51.

Dogging not available on ED6800A devices.

##### Fasteners

Standard on ED6800 devices: machine screws.

Optional on ED6800 devices: sex nuts and bolts; specify M54.

Optional on ED6800 and ED6800A devices: spanner head screws; specify M02.

##### Strikes

See Options and Accessories, page 31.

##### Trims and Functions

Through-bolted knob and operator trims available with wide range of functions. See Trims and Functions, page 26.

##### Cylinders

Cylinder not included unless specified. See How to Order, page 34.

##### Applications and Listings

See page 3.

##### Warranty

One-year limited.

#### Certification/Compliance

##### ANSI

Meets A156.3, Grade 1.

Meets A117.1 Accessibility Code.

##### C-UL US

All exit devices listed for safety as panic hardware; devices comply with UL 305 standards for panic hardware. 3-hour fire-rated devices listed as fire exit hardware for A label and less class 8' x 7'2" double doors. UL symbol on active head indicates listing.

Any retrofit or other field modification to a fire-rated opening can potentially impact the fire rating of the opening, and Corbin Russwin, Inc. makes no representations or warranties concerning what such impact may be in any specific situation. When retrofitting any portion of an existing fire-rated opening, or specifying

and installing a new fire-rated opening, please consult with a code specialist or local code official (Authority Having Jurisdiction) to ensure compliance with all applicable codes and ratings.

##### NFPA

All exit devices comply with NFPA 101 Life Safety Code. Fire-rated devices comply with NFPA 80 Fire Doors and Windows.

##### ADA

Exit devices, lever trims and pulls comply with Americans with Disabilities Act.

#### Finishes


BHMA 605	Bright Brass
BHMA 606	Satin Brass
BHMA 611	Bright Bronze
BHMA 612	Satin Bronze
BHMA 613	Oxidized Bronze, oil rubbed, available lacquered
BHMA 618	Bright Nickel Plated
BHMA 619	Satin Nickel Plated
BHMA 622	Flat Black Coated
BHMA 625	Bright Chromium Plated
BHMA 626	Satin Chromium Plated
626C	Satin Chromium Plated with MicroShield®
BHMA 629	Bright Stainless Steel
BHMA 630	Satin Stainless Steel
630C	Satin Stainless Steel with MicroShield®
BHMA 722	Black oxidized bronze, oil rubbed

# Concealed Vertical Rod Exit Features

ED6000

## ED6800 and ED6800A Concealed Vertical Rod Exit Devices









For use with metal doors only.  
1-3/4" door thickness only.



# CVR Trims and Functions

## ED6000

Concealed Vertical Rod Exit Device	ANSI Type	Accepts Trim/Function		Function Description (See Trim Designs Below)
		Type	ANSI No.	
ED6800	8	Exit Only	F01	- Exit only; no trim. (Accepts all trims listed below.)
ED6800A	8	Exit Only	F01	- 3-hour fire-rated exit only; no trim. (Accepts all trims listed below.)
For Passage, Dummy, Classroom and Nightlatch functions, see Trim Designs below.		Passage (10)	—	- Free at all times.
		Dummy (50)	F02	- Always free wheeling.
		Classroom (55)	F08/F11	- Free at all times, except when locked by key.
		Nightlatch (57)	F03/F04/ F09/F12	- Always rigid. Entrance by trim when latchbolt is retracted by key. Key removable only when locked.
ED6800	8	Latch hold back	F04	- Latchbolt held in retracted position by depressing bar and turning key. (Outside Cylinder Dogging.)

Pull Trim Design	Trim/Function			
	Passage	Dummy ANSI No. F02	Classroom ANSI No. F08/F11	Nightlatch ANSI No. F03/F04/ F09/F12
 <p><b>Belmont B5</b> Knob: Wrought reinforced Escutcheon: Cast Cylinder: 1-1/2" Mortise A02 Cam</p> 	B510	B550	B555	B557
 <p><b>Global G6</b> Knob: Wrought reinforced Escutcheon: Cast Cylinder: 1-1/2" Mortise A02 Cam</p> 	G610	G650	G655	G657
 <p><b>D Grip Operator 01</b> Grip: Extruded Escutcheon: Cast Cylinder: Mortise with A92 cam</p> 	N/A	0150	0155	0157 0156*
 <p><b>Round Grip Operator 02</b> Grip: Extruded Escutcheon: Cast Cylinder: Mortise with A92 cam</p> 	N/A	0250	0255	0257 0256*

\*Key also holds top and bottom latchbolts in retracted position for ANSI No. 04 function. Not available with ED6800A devices.

### ED66900 Series Electrically Controlled Mortise Exit Devices

#### Applications

This series offers the safety features of a heavy-duty mortise crossbar exit devices with the added security of an electrically controlled exit (ECE). Solenoid-operated units are designed for optimum versatility and flexibility, providing both power lock (fail safe) and power unlock (fail secure) functions in AC as well as DE systems. This devices is best used in:

- Stair tower doors
- Perimeter doors
- Security areas
- Computer areas
- Controlled environments


#### Advantages

- Proven reliability and durability of the Corbin Russwin Mortise Lockset
- Available as fail safe or fail secure
- Key always retracts latchbolt
- Integral solenoid
- Low voltage AC or DC systems available
- Accepts wide range of trims

#### ElectroLynx®

*ElectroLynx*, a new quick-connect feature of ASSA ABLOY Group companies, takes the guesswork out of installing electrified door hardware products.

It's ... hardwiring Made Easy. By using standard "plug and play" connectors, a simple "click" links power from the incoming source to electrified locking products, including hinges, locks, exit devices, magnetic holders, and strikes. What normally takes an hour or more can be connected in virtually minutes.



# ECE Features

## ED6000

### ED66900 Panic-Listed ECE Mortise Exit Device

**Features**

**Handing**

Field reversible device; specify hand.  
Mortise lock and strike are not reversible.

**Bar Length**

Easily field cut to size.  
Standard 36" bar fits doors up to 36" (914mm).  
Optional 48" bar fits doors up to 48" (1219mm); specify W048.

**Door Thickness**

1-3/4" (44mm).  
Optional: 2" (51mm) and 2-1/4" (57mm); to order specify D200 or D214.

**Backset**

2-3/4" (70mm).

**Stile**

Minimum width: 5" (127mm).

**Latchbolt**

Brass, 3/4" (19mm) throw.

**Auxiliary Latch**

Brass.

**Front**

8" x 1-1/4" (203mm x 32mm) heavy gauge steel.  
Accommodates flat doors and doors beveled 1/8" to 2" (3mm to 51mm).

**Materials**

Brass, bronze or stainless steel.

**Cases**

Heavy wrought, 7-1/4" x 2-9/16" (184mm x 65mm).

**Crossbar**

Standard: 13/16" x 1-3/8" (20mm x 35mm) oval seamless tubing.  
Optional: reinforced crossbar or stainless steel crossbar; see Quick Codes, page 36.

**Dogging**

Dogging standard.  
Optional: less dogging. Specify M51.

**Fasteners**

Standard: machine screws.  
Optional: sex nuts and bolts; specify M54.  
Optional: spanner head screws; specify M02.

**Strike**

Standard: ANSI strike.  
Optional: open back strike and ANSI wrought strike box available; see Options and Accessories, page 32.

**Trim**

Accepts trims listed on pages 20-22.

**Cylinders**

Cylinder not included unless specified. See How to Order, page 34.

**Operating Current**

12VAC	0.8 AMPS
12VDC	0.8 AMPS
24VAC	0.4 AMPS
24VDC	0.4 AMPS

See How to Order, page 35.

**Warranty**

One-year limited.

**Certification/Compliance**

**ANSI**

Meets A156.3, Grade 1.

**C-UL US**

All exit devices listed for safety as panic hardware; devices comply with UL 305 standards for panic hardware. UL symbol on active head indicates listing.

**NFPA**


All exit devices comply with NFPA 101 Life Safety Code.

**ADA**

Exit devices, lever trims and pulls comply with Americans with Disabilities Act.



**Finishes**

BHMA 605	Bright Brass
BHMA 606	Satin Brass
BHMA 611	Bright Bronze
BHMA 612	Satin Bronze
BHMA 613	Oxidized Bronze, oil rubbed, available lacquered
BHMA 618	Bright Nickel Plated
BHMA 619	Satin Nickel Plated
BHMA 622	Flat Black Coated
BHMA 625	Bright Chromium Plated
BHMA 626	Satin Chromium Plated
626C	Satin Chromium Plated with MicroShield®
BHMA 629	Bright Stainless Steel
BHMA 630	Satin Stainless Steel
630C	Satin Stainless Steel with MicroShield®
BHMA 722	Black oxidized bronze, oil rubbed







The following functions are locked when power is on (Fail Safe).

Inside	Outside	Function	Function Description
		<b>ED66902</b>	<ul style="list-style-type: none"> <li>- When energized, solenoid locks outside trim; thumbpiece is then free-acting and disengaged.</li> <li>- Key retracts latchbolt at all times.</li> <li>- Mortise Lock No. MLE10.</li> </ul>
		<b>ED66904</b>	<ul style="list-style-type: none"> <li>- When energized, solenoid locks outside trim; knob or lever is then free-acting and disengaged.</li> <li>- Key retracts latchbolt at all times.</li> <li>- Mortise Lock No. MLE10.</li> </ul>

The following functions are unlocked when power is on (Fail Secure).


Inside	Outside	Function	Function Description
		<b>ED66901</b>	<ul style="list-style-type: none"> <li>- When energized, solenoid unlocks outside trim.</li> <li>- Thumbpiece retracts latchbolt.</li> <li>- Key retracts latchbolt at all times.</li> <li>- Mortise Lock No. MLE11.</li> </ul>
		<b>ED66903</b>	<ul style="list-style-type: none"> <li>- When energized, solenoid unlocks outside trim.</li> <li>- Knob or lever retracts latchbolt.</li> <li>- Key retracts latchbolt at all times.</li> <li>- Mortise Lock No. MLE11.</li> </ul>

# Options and Accessories

## ED6000


### Rim Strikes

(Screws Included)




#### Rim Strike

Standard on ED6200 devices. For doors with 1/2" (13mm) or 5/8" (16mm) stop. Adjustable to compensate for shrinkage and swelling of door. Nylon anti-friction inserts for quieter operation. 3-1/4" x 1-1/16" (82mm x 27mm). To order separately, specify 145F55. 1/8" (3mm) shim available for 1/2" (13mm) stop; specify 184F82.




#### Rim x Vertical Rod Strike

Required for ED6200 devices when used with ED6400 device on a pair of doors. To order with device, specify option S02. To order separately, specify 467F73.




#### Mortised Adjustable Rim Strike

Optional for ED6200 devices only. Adjustable to compensate for shrinkage and swelling of door. 3-3/4" x 1-9/16" (95mm x 40mm). To order with device, specify option S04. To order separately specify 142F43.



#### Fire-Rated Rim Strike

Standard on ED6200A devices. Steel with black nylon coating. Surface application; reversible, adjustable. 4-3/8" x 1-9/32" (111mm x 32mm). To order separately, specify 499F59.




#### Open Rim Strike

Optional for ED6200 devices. Adjustable to compensate for shrinkage and swelling of door. Nylon anti-friction inserts for quieter operation. 3-1/4" x 1-3/32" (82mm x 28mm). To order with device, specify S05. To order separately, specify 145F56.


### Vertical Rod Strikes

(Screws Included)




#### Top Strike for Latch Hold-Back

Standard on ED6400 devices with latch hold-back. 2-3/32" x 1-3/4" x 2-5/32" (53mm x 44mm x 55mm) high. To order separately, specify 392F24.




#### Non-Hold-Back Top Strike

Standard on ED6400 devices without latch hold-back. 1-1/2" x 1-3/4" x 7/8" (38mm x 44mm x 22mm) high. To order separately, specify 392F22.




#### Flush Transom Strike Bracket

Optional for ED6400 devices when mounting top strike on flush transom. To order with device, specify option M67. To order separately, specify 176F65.




#### Surface Projecting Bottom Strike

Standard on ED6400 devices. 2-9/16" x 19/32" x 5/8" (65mm x 15mm x 16mm) high. To order separately, specify 502F96.




#### Flush Bottom Strike

Optional for ED6400 devices. 3-1/2" x 1-3/4" x 7/8" (99mm x 44mm x 22mm) deep. To order with devices, specify option S03. To order separately, specify 392F28.



#### Bottom Strike for Threshold

Optional on ED6400A devices. For use with threshold. To order with device, specify option S06. To order separately, specify 304F34.




#### Bottom Strike

Standard on ED6400A devices. To order separately, specify 502F75.


### Concealed Vertical Rod Strikes

(Screws Included)




#### Top Strike

Standard on ED6800 devices. To order separately, specify 503F55.



#### Bottom Strike

Standard on ED6800 and ED6800A devices. To order separately, specify 503F52.




#### Fire-Rated Top Strike

Standard on ED6800A devices. To order separately, specify 503F56.

# Options and Accessories


## ED6000

### Mortise Strikes




#### Straight Lip ANSI Strike

Standard on ED6600 and ED6600A. On stainless steel exit devices, stainless steel strike furnished standard. 4-7/8" x 1-1/4" x 1-1/8" (124mm x 32mm x 28mm) lip to center, for 1-3/4" (44mm) doors. To order separately, specify Part No.



#### Open Back Strike

Optional for use with ED6400 x ED6600 devices on a pair of doors. See How to Order, page 35. To order separately, specify Part No. x Door Thickness x Finish.



#### ANSI Wrought Strike Box

Optional for use with Mortise Strike on ED6600 and ED6600A devices; specify option M17. To order separately, specify 120F76-8.

Hand	Part No.
RHR	405L14
	240L51 (stainless steel)
LHR	405L13
	240L50 (stainless steel)

Hand	Door Thickness	Part No.
LHR	1-3/4"	411L62 016 FIN
	2"	411L62 018 FIN
	2-1/4"	411L62 020 FIN
RHR	1-3/4"	411L63 016 FIN
	2"	411L63 018 FIN
	2-1/4"	411L63 020 FIN

### Filler Plates

Optional for use on stock metal doors when required. To order, specify Part No. x Finish.

Front 334F99-8 600	Strike 236L708018	Front 077F19-8 600

### 500 Series and 900 Series Removable Mullions

The 500 series and 900 series mullions are used to install two ED7200 Rim Exit Devices in a double door opening. They may be quickly and easily removed, then reinstalled, when a full double door opening is temporarily required. The 500 series and 900 series mullions meet ANSI A156.3, Type 22.

#### Materials and Finish

Steel mullion with malleable iron top and bottom plates; furnished with zinc plated fasteners for metal frames and concrete floors. May be cut, drilled and tapped in the field for Rim Exit Devices. The 500 series mullions are primed for painting, BHMA 600, grey and the 900 series mullions are primed for painting, BHMA 600, red.

### 500 Series Mullions - How to Order Removable Mullions

UL Fire Rating <sup>1</sup>	Mullion Opening Height <sup>2</sup>	Catalog Number
3-Hour	Up to 7'2"	507
Panic Only	Up to 8'0"	508
Panic Only	Up to 10'0"	510

Notes:

1. UL label on mullion indicates listing.
2. May be field cut for doors.

### 900 Series Mullions - How to Order Removable Mullions

UL Fire Rating <sup>1</sup>	Mullion Opening Height <sup>2</sup>	Catalog Number
Panic Only	Up to 7'0"	907
Panic Only	Up to 8'0"	908
Panic Only	Up to 10'0"	910
3-Hour	Up to 7'0"	907A
3-Hour	Up to 8'0"	908A


#### Key Removable Mullions

UL Fire Rating <sup>1</sup>	Mullion Opening Height <sup>2</sup>	Catalog Number
1-1/2 Hour	Up to 7'0"	907BKM <sup>3</sup>
1-1/2 Hour	Up to 8'0"	908BKM <sup>3</sup>
Panic Only	Up to 10'0"	910KM <sup>3</sup>

Notes:

1. UL label on mullion indicates listing.
2. May be field cut for doors.
3. Cylinder and collars not included, specify separately. See Cylinders on page 34.

### 500 Mullion



### 900 Series Mullions - Options M95- Spacer Block

Recommended for double rabbeted frames where the stop face width is less than the mounting hole spacing and also for door frames 5-3/4" (176mm) or less. To order with a mullion, specify M95. To order separately, specify Part No. 683F29-8.


#### M96- Angle Bracket

Recommended for any header configuration with less than 3" (76mm) of mounting surface. To order with a mullion, specify M96. To order separately, specify Part No. 655F63-8.

#### M57- Mullion Stabilizer Kit

Controls the movement of the mullion. Recommended for opening over 7' high, or whenever door movement must be minimized. To order with mullion, specify M57. To order separately, specify Part No. 653F11-1 x 695 or 628.

### 900 Mullion



# Cylinders

## ED6000


### Cylinders

- L4 keyway standard; specify other keyways.
- Specify Collar.
- To order with Exit Device, see How to Order, page 35.

- To order separately, specify Part No. x Keyways Finish (e.g., 3000-200 x L4 x 626).

Cylinder Type	Part No.	Description
Rim	3000-200	6-pin, horizontal tailpiece
	3000-200-7	7-pin, horizontal tailpiece
	3010-200	6-pin, horizontal tailpiece, Security
	3012-178	6-pin, blockout function, Security
	3020-200	7-pin, Pyramid High Security
	3027-200	7-pin Pyramid Security
	3027-178	7-pin Pyramid IC Security
	3030-178	7-pin, Pyramid IC High Security
	3040-178	6-pin SFIC Rim Housing
	3040-178-7	7-pin SFIC Rim Housing
	3060-200	6-pin, master ring
	3070-178	6-pin, interchangeable core (IC) less core
	3070-178-7	7-pin, IC less core
	3080-178	6-pin, IC
	3080-178-7	7-pin, IC
	3090-178	6-pin, Security IC
	1000-112-A02	6-pin, 1-1/2" straight cam
	1000-112-A02-7	7-pin, 1-1/2" straight cam
	1000-114-A02-7	7-pin, 1-1/4" straight cam
	1000-114-A92-7	7-pin, 1-1/4" (O1 and O2 trims only)
	1000-118-A02	6-pin, 1-1/8" straight cam
	1000-118-A92	6-pin, 1-1/8" (O1 and O2 trims only)
	1000-134-A02	6-pin, 1-3/4" straight cam
	1000-134-A02-7	7-pin, 1-3/4" straight cam
	1010-112-A02	6-pin, 1-1/2" Security straight cam
1010-118-A02	6-pin, 1-1/8" Security, straight cam	
1010-118-A92	6-pin, 1-1/8" Security (O1 and O2 trims only)	
1010-134-A02	6-pin, 1-3/4" Security straight cam	
1012-114-A02	6-pin, 1-1/4" Security with blockout	
1012-114-A92	6-pin, 1-1/4" Security blockout (O1 and O2 trims only)	
1020-112-A02	7-pin, Pyramid High Security 1-1/2"	
1020-114-A02	7-pin, Pyramid High Security 1-1/4"	
1027-112-A02	7-pin, Pyramid Security IC 1-1/2"	
1027-114-A02	7-pin, Pyramid Security 1-1/4"	
1030-114-A02	7-pin, Pyramid IC High Security 1-1/4"	
1037-114-A02	7-pin, Pyramid Security IC 1-1/4"	
1040-112	7-pin, 1-1/2" SFIC Mortise Housing	
1040-114	6-pin, 1-1/4" SFIC Mortise Housing	
1040-134	7-pin 1-3/4" SFIC Mortise Housing	
1040-138	7-pin, 1-3/8" SFIC Mortise Housing	
1070-114-A02	6-pin, 1-1/4" IC less core	
1080-112-A02	6-pin, 1-1/2" IC straight cam	
1080-112-A02-7	7-pin, 1-1/2" IC straight cam	
1080-114-A02	6-pin, 1-1/4" IC straight cam	
1080-134-A02	6-pin, 1-3/4" IC straight cam	
1080-134-A02-7	7-pin, 1-3/4" IC straight cam	
1090-112-A02	6-pin, 1-1/2" IC Security straight cam	
1090-114-A02	6-pin, 1-1/4" IC Security straight cam	
1090-134-A02	6-pin, 1-3/4" IC Security straight cam	
1000-118-A62	6-Pin	
1000-114-A62-7	7-Pin	
1080-114-A62	6-Pin, IC	
1080-112-A62-7	7-Pin, IC	
1020-114-A62	7-pin, Pyramid High Security	
1027-114-A62	7-pin, Pyramid Security	
1030-114-A62	7-pin, Pyramid High Security IC	
1037-114-A62	7-pin, Pyramid Security IC	
1010-118-A62	Security	
1090-114-A62	Security IC	
1070-114-A62	6-pin, IC, less core	
1070-112-A62-7	7-pin, IC, less core	


### 900 Series Key Removable Mullion Mortise Cylinders



### 900 Series Key Removable Mullion Cylinder Collar Packet

Mullion Series	Cylinder Length and Type			
	1-1/8"	1-1/4"	1-1/4" IC	1-1/2" IC
907BKM	610F01*	447F43*	609F37*	
908BKM				
910KM				

Note: Cylinder collar packets contain a collar and spring washer. \*Specify finish when ordering packets.



### Rim Exit Device

Quantity	Exit Device	Finish	Hand	Misc. Options
27	ED6200	630	RHR	M51-M54

### Removable Mullion

Quantity	Mullion
9	507

### Trim Only (For Rim Exit Device)

Quantity	Trim/Function	Finish	Hand	Door Thickness
34	L210	625	RHR	D214

### Where to find ordering information and Quick Codes

Functions and Trims	Pages
Rim and Vertical Rod	Pages 9-12
Fire-Rated Rim	Pages 15-17
Mortise	Pages 20-23
Concealed Vertical Rod	Page 26
Removable Mullion	Page 33
Cylinder and Keying	Page 36
Miscellaneous Options	Page 36
Finish	Page 37
Handing	Page 37
Door Thickness	Page 37
Strike	Page 37
Door Width	Page 37
Door Height	Page 37

### Rim Exit Device with Trim

Quantity	Exit Device	Trim/Function	Finish	Hand	Door Thickness	Optional Strike	Door Width	Misc. Options
18	ED6200	N355	605	LHR	D200	S04	W048	M53

### Contract/Detailed Order - Rim Exit Device with Trim


Quantity	Keypad	Exit Device	Trim/Function	Finish	Hand	Door Thickness	Door Width	Door Options	Misc. Options	Cylinder Keying	Keyway
68	AA1	ED6200	C255	626	RHR	D200	W048	M50-M54	7P	VKC3	59A1

## Ordering Examples - ED66900 Series

**Lock Only** (Includes lock case, armored front, strike and screw pack)

Quantity	Mortise Lock	Finish	Hand	Voltage
16	MLE10	626	LHR	24D

### Handing



Note: Arrow indicates secure side of door.

### Contract/Detailed Order

Quantity	Keypad	Exit Device	Trim/Function	Finish	Hand	Voltage	Options	Misc. Options	Cylinder Keying	Keyway
34	AA1	ED66904	C3M55	626	RHR	12A	M53-M54	6P	VKC3	59A1

# Quick Codes

## ED6000

### Cylinder and Keying

Description	Specify
Conventional 6-pin	6P
Conventional 7-pin	7P
Pyramid Security fixed core <sup>4</sup>	PS
Pyramid Security IC <sup>1</sup>	PCS
Pyramid High Security fixed core <sup>4</sup>	PHS
Pyramid High Security IC <sup>1</sup>	PCHS
Pyramid IC with temporary construction core <sup>1</sup>	CTP
Pyramid IC with temporary disposable core <sup>1</sup>	CTPD
Pyramid IC less core <sup>1</sup>	CLP
Security	HS
Security IC <sup>1</sup>	CHS
Blockout function cylinder	BO
IC 6-pin <sup>1</sup>	C6
IC 6-pin with temporary construction core (Red) <sup>1</sup>	CT6R
IC 6-pin with temporary construction core (Blue) <sup>1</sup>	CT6B
IC 6-pin with temporary construction core (Green) <sup>1</sup>	CT6G
IC 6-pin with temporary construction core <sup>1</sup>	CT6
IC 6-pin with temporary disposable core <sup>1</sup>	CT6D
IC 6-pin less core <sup>1</sup>	CL6
SFIC 6-pin with Less Core	CLS6
SFIC 6-pin with SFIC disposable temporary core	CT6SD
IC 7-pin <sup>1,2</sup>	C7
IC 7-pin with temporary construction core (Red) <sup>1</sup>	CT7R
IC 7-pin with temporary construction core (Blue) <sup>1</sup>	CT7B
IC 7-pin with temporary construction core (Green) <sup>1</sup>	CT7G
IC 7-pin with temporary construction core <sup>1,2</sup>	CT7
SFIC 7-pin with Less Core	CLS7
SFIC 7-pin with SFIC disposable temporary core	CT7SD
IC 7-pin with temporary disposable core <sup>1,2</sup>	CT7D
IC 7-pin less core <sup>1,2</sup>	CL7
Less master ring cylinder <sup>3</sup>	MR-LC
Master Ring <sup>3</sup>	MR
0-bitted with 2 blank keys	(standard)
Keyed random	KR
Construction master keyed	CMK (not available for Pyramid)
No keying data stamped on key or cylinder	VKC0
Keys only	VKC1
Cylinders and keys (not for HS, CHS, PHS or PCHS)	VKC2
Cylinders only (not for HS, CHS, PHS or PCHS)	VKC3
Concealed key control (CKC)	
- CKC cylinders with VKC keys	CKC2
- CKC cylinders only (not for HS, CHS, PHS or PCHS)	CKC3
2 keys per lock	(standard)
More than 2 keys	KY# (e.g., KY6)

1. Not available on O1 and O2 trim.

2. Rim only.

3. Complete rim and vertical rod devices are available with master ring trim. However, complete master ring mortise devices are discontinued. Master ring mortise trim is available to support old master ring mortise devices in the field.

4. Not available in ED6600, A4M, C3M, D3M, E3M, L3M, N4M, PR3M, R3M, B4M, G5M trims.

### Miscellaneous Options



Description	Specify
ANSI wrought strike box	M17
Knurling outside & inside (trim & device; not available with M50)	M20
Knurling outside only (trim side)	M21
Knurling inside only (device side; not available with M50)	M22
Abrasive coat outside and inside (trim and device)	M23
Abrasive coat inside only (device side)	M24
Abrasive coat outside only (trim side)	M25
Stainless steel crossbar (not available with M20 or M22)	M50
Less dogging	M51
Steel reinforced crossbar	M53
Sex nuts and bolts (SNBs)	M54
Mullion stabilizer kit	M57
Shim for 2-3/4" backset on doors with 1/2" stop (rim devices only)	M59
Freelatching latchbolts (ED6400 devices only)	M65
Flush transom bracket	M67



### Strike

Description	Specify
Rim	
Mortised adjustable	S04
Open	S05
Rim x Vertical Rod	S02
Vertical Rod	
Flush bottom (ED6400 devices only)	S03
3-hour fire-rated bottom for use with threshold	S06
Mortise	
Open back strike	
1-3/4" door thickness	SB134
2" door thickness	SB200
2-1/4" door thickness	SB214
Straight Lip ANSI Strike	
1-3/4" door thickness	(standard)
2" door thickness	SS114
2-1/4" door thickness	SS138

### Finish

Description	Specify
US3 Bright Brass	605
US4 Satin Brass	606
US9 Bright Bronze	611
US10 Satin Bronze	612
US10B Dark Oxidized Satin Bronze, oil rubbed	613
US14 Bright Nickel Plated	618
US15 Satin Nickel Plated	619
US19 Flat Black Coated	622
US26 Bright Chromium Plated	625
US26D Satin Chromium Plated	626
— Satin Chrome Plated with MicroShield® 	626C
US32 Bright Stainless Steel	629
US32D Satin Stainless Steel	630
— Satin Stainless Steel with MicroShield® 	630C
— Black oxidized bronze, oil rubbed	722

### Door Height

Door	Specify
7'2" (ED6400A and ED6800A devices)	(standard)
7'6" (ED6400 devices)	(standard)
8'6" (ED6800 devices)	(standard)
10'0" (ED6400 devices only)	H1000
10'8" (ED6800 devices only)	H1008

### Handing

Hand	Specify
Right Hand Reverse	RHR
Left Hand Reverse	LHR

### Door Width

Door	Specify
36" (914mm)	(standard)
48" (1219mm)	W048

### Door Thickness

Door	Specify
1-3/4" (44mm)	(standard)
2" (51mm) (except ED6800)	D200
2-1/4" (57mm) (except ED6800)	D214

### Voltage

Door	Specify
12 volt alternating current	12A
12 volt direct current	12D
24 volt alternating current	24A
24 volt direct current	24D

# Helpful Terms

## ED6000

### **Abrasive Coat**

Hard granular material applied to provide a non-slip tactile surface for the visually impaired.

### **Active Door**

In a pair of doors, the door that is operable from the trim side.

### **Astragal**

A vertical member applied to one or both sides of a pair of doors at the meeting edges. The astragal closes the gap between the two doors.

### **Coordinator**

A device used on a pair of doors to ensure that the inactive door closes before the active door.

### **Deadlocking Latch**

A supplemental latch that automatically deadlocks the latchbolt when pressure is applied to it.

### **Dogging**

A mechanism that allows the latchbolt to remain retracted, permitting the door to operate as if it were a push-pull; it cannot be used on fire-rated exit devices.

### **Double Egress**

A pair of doors of the same hand that swing in opposite directions, commonly found in corridors.

### **Dummy Trim**

Trim only. Usually used on the inactive door of a pair of doors for design balance.

### **Exit Device (Panic Hardware)**

A door locking device with a pushpad or crossbar which, when pressed, allows instant exit (egress).

### **Fire Exit Hardware**

An exit device listed by an independent testing laboratory as meeting panic, fire and hose stream test standards; used on fire rated openings.

### **Hand**

The direction a door swings.

### **Inactive Door**

In a pair of doors, the door that is inoperable from the trim side.

### **Latchbolt**

A lock component that has a beveled end and projects into a strike, holding the door in a closed position.

### **Mullion**

A fixed or removable vertical member that divides a door opening and provides a latch surface for a pair of rim exit devices.

### **Narrow Stile Door**

Usually a door having a stile of less than 2-3/4" wide, commonly seen on aluminum or glass front applications.

### **Open Back Strike**

For mortise exit devices, used on the inactive door (usually the vertical rod door) of a pair of doors that swing in the same direction. It permits the inactive door to open or close independently.

### **Reversible**

Pertains to a product that may be changed in the field to accommodate any hand of the door.

### **Shim Kit**

Pieces of metal that permit mounting of an exit device on a door that has a surface projecting vision light (glass bead) molding.

### **Split Astragal**

An astragal that is split through the middle on a pair of doors, allowing both doors to operate independently.

### **Threshold**

A strip fastened to the floor beneath a door. It serves as a stop, prevents heat loss, and provides a strike location for latching the bottom rod of a vertical rod exit device.

### **Trim**

A knob, lever, pull, or thumbpiece used on the outside of an exit device door to control access to an area.

### **Universal Exit Device**

An exit device that may be used on doors of either hand without any modifications.

## **Keying and Cylinder Terms**

### **Blockout Cylinder**

A cylinder which allows all keys to be temporarily blocked from operating. It is set by a blockout key.

### **Concealed Key Control (CKC)**

The marking of standard key symbols on a cylinder in a location that is not visible once the cylinder is installed.

### **Construction Master Keying (CMK)**

A cylinder preparation that allows temporary access by construction personnel.

### **Control Key**

A key used to remove and install interchangeable cores.

### **Cylinder**

A lock component containing the combination that determines which keys will operate.

### **Security Cylinder**

A cylinder which provides extra resistance to picking and unauthorized duplication of keys.

### **Interchangeable Core (IC)**

A cylinder which can be removed and installed quickly with a control key by non-skilled personnel when rekeying is required.

### **Key Symbol**

A letter/number combination in standard industry format (e.g., 1AA, AA1, etc.) which indicates exactly how a key or cylinder fits into a keying system.

### **Keyway**

The opening in a cylinder plug through which the key enters.

### **Master Keying**

Preparation of a cylinder to operate with keys of different levels of access.

### **Visual Key Control (VKC)**

The marking of standard key symbols on keys and on the visible portion of the front of a cylinder.

### Suggested Specification ED6000 Series

All exit devices shall be ED6000 Series Crossbar Exit Devices as manufactured by Corbin Russwin Architectural Hardware.

The maximum projection shall be 5-3/4", and 4-1/2" when crossbar is depressed. Exit devices shall have matched twin cases mounted with concealed fastening screws and shall be constructed of brass, bronze or stainless steel. Non-matched twin cases shall not be acceptable. Crossbar lever arms shall be drop forged. Devices shall be field reversible.

Crossbars shall be oval-shaped and shall be a minimum of .065" thick. Crossbars shall interlock into the lever arms by expansion collects and interlocking roll pins. Crossbars attached with rivets shall not be acceptable. Reinforced crossbars and stainless steel crossbars shall be available. All exit devices shall be easily field sized to accommodate various door widths.

Panic listed exit devices shall have dogging standard. Dogging screws shall seat into heat-treated pivots for long life and minimum wear. Panic listed devices shall be available less dogging.

All exit devices shall have ample allowances for easy alignment.

Trims shall be through-bolted with concealed fasteners. Escutcheon, rose and pull trims shall be constructed of brass, bronze or stainless steel. All lever trims shall use cast levers. Wrought levers shall not be acceptable. Lever trims shall match those on Corbin Russwin Mortise and Cylindrical Locksets.

All devices and trims shall be furnished in architectural finishes.

All devices shall be listed by Underwriters Laboratories (UL) for safety as panic hardware. Fire-rated devices shall be UL listed for A label and lesser class doors, 4' x 7'2" single and 8' x 7'2" pair.

Certification:  
ANSI A156.3, Grade 1  
ANSI A117.1 Accessibility Code  
California State Fire Marshal pursuant to section 13144.1 of the California Health and Safety Code.

All devices, trims and cylinders shall be from one manufacturer.

All mechanical devices and trims shall carry a one-year limited warranty.

All electro-mechanical devices shall carry a two-year limited warranty.

### Suggested Specification ED66900 Series

All exit devices shall be ED66900 Series Electrically Controlled Exit Devices, as manufactured by Corbin Russwin Architectural Hardware.

All mortise lock functions shall be available in one size case, manufactured from heavy-gauge steel, minimum thickness 3/32", completely chrome plated for corrosion resistance and lubricity of parts. Cases shall be closed on all sides to protect internal parts. Locks shall have adjustable, beveled and armored fronts, standard 2-3/4" backset, a full 3/4" throw two-piece mechanical anti-friction latchbolt, and shall be available for 1-3/4", 2" and 2-1/4" thick doors. Internal parts shall be heavy gauge steel, zinc dichromate plated for corrosion resistance.

Devices shall fit ANSI standard strike preparation. Other than for wiring, no special door or frame preparation shall be required.

Devices shall be available 12 or 24 volt, AC or DC, and fail safe or fail secure.

Mechanical cylinder override shall be available. Optional cylinders shall include interchangeable core, security and blockout types.

Lock trim (knob, lever or thumbpiece) shall be through-bolted through the lockcase to ensure correct alignment and proper operation.

Certification:  
ANSI A156.3, Grade 1  
ANSI A117.1 Accessibility Code (lever handle trim)  
California State Fire Marshal pursuant to section 13144.1 of the California Health and Safety Code.

All devices, trims and cylinders shall be from one manufacturer.

All mechanical devices and trims shall carry a one-year limited warranty.

All electro-mechanical devices shall carry a two-year limited warranty.



**ASSA ABLOY**

**In U.S.**

Corbin Russwin  
Architectural Hardware  
225 Episcopal Road  
Berlin, CT 06037  
Phone: 800-543-3658  
Fax: 800-447-6714  
[www.corbinruswin.com](http://www.corbinruswin.com)

**In Canada**

ASSA ABLOY Door  
Security Solutions Canada  
160 Four Valley Drive  
Vaughan, Ontario  
Canada L4K 4T9  
Phone: 800-461-3007  
Fax: 1-905-738-2478  
[www.assaabloy.ca](http://www.assaabloy.ca)

For more information regarding Corbin Russwin Locksets, Exit Devices, Door Controls and Key Systems, contact your authorized Corbin Russwin Distributor or Sales Representative.



**MicroShield®**

As part of their promise to provide innovative solutions to their customers, certain ASSA ABLOY Group brands offer the MicroShield® technology, a silver-based antimicrobial coating designed to inhibit the growth of bacteria. MicroShield® is a registered trademark of Yale Security Inc., an ASSA ABLOY Group company.

Hardwiring Made Easy™



**ElectroLynx®**

As part of their promise to provide innovative, fast and effective high security solutions to their customers, certain ASSA ABLOY Group brands offer ElectroLynx®, a universal quick-connect system that simplifies the electrification of the door opening. ElectroLynx® is a registered trademark of ASSA ABLOY Inc.

Corbin Russwin and Design® is a registered trademark of Corbin Russwin Inc., an ASSA ABLOY Group company. These materials are protected under US copyright laws. All contents current at time of publication. Corbin Russwin, Inc., an ASSA ABLOY Group company reserves the right to change availability of any item in this catalog, its design, construction, and/or its materials. Other products brand names may be trademarks or registered trademarks of their respective owners and are mentioned for reference purposes only. Copyright© 2003, 2012 Corbin Russwin Inc., an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Corbin Russwin, Inc. is prohibited.

ASSA ABLOY is the global leader in door opening solutions, dedicated to satisfying end-user needs for security, safety and convenience.