



PULLS - CLOSET / POCKET / SLIDING DOOR



22N Concealed Edge Pull

Certification: Meets ANSI A156.14 for D2801
 Size: 31/32" x 4-1/4" x 3/8" thick (25 mm x 108 mm x 9.5 mm)
 Lever Extension: 2-19/32" (66 mm)
 Materials: Brass
 Finishes: US3, US26D
 Fasteners: Two (2) #6 x 3/4" FPHWS



330D Pocket Door Latch

Certification: Meets ANSI A156.14 for D0821
 Size: 2-3/4" x 2-1/2" (70 mm x 64 mm)
 Extension of Finger Piece: 1-3/8" (35 mm)
 Materials: Brass
 Finishes: US3, US5, US10B, US15A, US19, US26, US26D
 Fasteners: Two (2) #6 x 5/8" OPHWS
 Notes: For use with 1-3/8" - 1-3/4" (35 mm - 45 mm) door



330L Pocket Door Privacy Latch

Certification: Meets ANSI A156.14 for D0831
 Size: 2-3/4" x 2-1/2" (70 mm x 64 mm)
 Extension of Finger Piece: 1-3/8" (35 mm)
 Strike Size: 1" x 2-1/4" (25 mm x 57 mm)
 Materials: Brass
 Finishes: US3, US5, US10B, US15, US15A, US19, US26, US26D
 Fasteners: Two (2) #6 x 5/8" OPHWS and two (2) #6 x 3/4" FPHWS
 Notes: For use with 1-3/8" (35 mm) door



330M Pocket Door Privacy Latch

Certification: Meets ANSI A156.14 for D0831
 Size: 2-3/4" x 2-1/2" (70 mm x 64 mm)
 Extension of Finger Piece: 1-3/8" (35 mm)
 Strike Size: 1" x 2-1/4" (25 mm x 57 mm)
 Materials: Brass
 Finishes: US3, US5, US10B, US15, US15A, US19, US26, US26D
 Fasteners: Two (2) #6 x 5/8" OPHWS and two (2) #6 x 3/4" FPHWS
 Notes: For use with 1-3/4" (45 mm) door



2610 Flush Cup Finger Pull

Overall Diameter: 31/32" (24.5 mm)
 Finger Pull Diameter: 3/4" (19 mm)
 Pull Clearance: 5/16" (8 mm)
 Projection: 1/32" (.8 mm)
 Materials: Solid brass
 Finishes: US3, US4, US5, US10A, US15, US15A, US26, US26D, ABA
 Notes:

- For use on bi-fold, by-pass or pocket applications
- Built-in prong design eliminates the need for screws or brads



PULLS - CLOSET/POCKET/SLIDING DOOR



2620

Flush Cup Pull

Overall Diameter: 2-1/16" (52 mm)
 Finger Pull Diameter: 1-11/16" (43 mm)
 Pull Clearance: 11/32" (8.7 mm)
 Projection: 5/64" (2 mm)
 Materials: Solid brass
 Finishes: US3, US4, US5, US10A, US15, US15A, US26, US26D, ABA
 Notes:

- For use on bi-fold, by-pass or pocket applications
- Built-in prong design eliminates the need for screws or brads



2630

Flush Cup Pull

Overall Diameter: 2-7/16" (62 mm)
 Finger Pull Diameter: 2-1/16" (52 mm)
 Pull Clearance: 11/32" (8.7 mm)
 Projection: 3/32" (2.4 mm)
 Materials: Solid brass
 Finishes: US3, US4, US5, US10A, US15, US15A, US26, US26D, ABA
 Notes:

- For use on bi-fold, by-pass or pocket applications
- Built-in prong design eliminates the need for screws or brads



2640

Oblong Flush Pull

Size: 1-5/16" x 2-3/4" (33 mm x 70 mm)
 Cup Clearance: 5/16" (8 mm)
 Materials: Solid brass
 Finishes: US3, US4, US5, US10A, US15, US15A, US26, US26D, ABA
 Fasteners: Two (2) #6 x 5/8" OPHWS
 Notes: For use on bi-fold, by-pass or pocket applications



9558

Wood Knob

Diameter: 1-1/2" (38 mm)
 Materials: Solid wood
 Notes:

- For use on bi-fold applications
- Will accept paint or stain



9566

Knob

Diameter: 1-1/4" (32 mm)
 Projection: 1" (25 mm)
 Materials: Die Cast Zinc
 Finishes: US3, US4, US5, US10A, US10B, US15, US15A, US26, US26D
 Fasteners: One (1) 8-32 x 1-3/4" PPHMS and one (1) 8-32 x 2" PPHMS
 Notes: For use on bi-fold applications on doors 3/4" (19 mm) to 1-3/8" (35 mm) thick



PULLS - CLOSET/POCKET/SLIDING DOOR



9567

Rose

- Base Diameter: 1-3/4" (45 mm)
 Projection: 15/32" (12 mm)
 Materials: Die cast zinc
 Finishes: US3, US4, US5, US10A, US10B, US15, US15A, US26, US26D
 Fasteners: One (1) 8-32 x 1-3/4" PPHMS and one (1) 8-32 x 2" PPHMS
 Notes:
 - For use on bi-fold applications on doors 3/4" (19 mm) to 1-3/8" (35 mm) thick
 - For use with 9566 knob



9865

Flush Cup Pull

- Overall Diameter: 1-31/32" (50 mm)
 Finger Pull Diameter: 1-19/32" (40 mm)
 Pull Clearance: 11/32" (8.7 mm)
 Projection: 5/64" (2 mm)
 Materials: Tan color ABS plastic
 Notes:
 - For use on bi-fold, by-pass or pocket applications
 - Built-in prong design eliminates the need for screws or brads



9882

Pocket Door Edge Pull

- Face Plate Size: 3/4" x 3 - 7/8" (19 mm x 98 mm)
 Finger Pull Extends: 3/4" (19 mm)
 Materials: Solid brass
 Finishes: US3, US4, US10, US10B, US26, US26D
 Fasteners: Two (2) #6 x 5/8" FPHWS
 Notes:
 - Ideal for narrow and standard door thicknesses
 - Automatic spring return



9884

Pocket Door Edge Pull

- Faceplate: 21/32" x 3-1/2" (16.5 mm x 89 mm)
 Finger Pull Extends: 1-1/16" (27 mm)
 Materials: Die cast zinc
 Finishes: US3
 Fasteners: Two (2) #6 x 5/8" FPHWS
 Notes: Ideal for narrow and standard door thicknesses